



according to 1907/2006/EC, Article 31

Printing date 01.02.2023 Version number 3 (replaces version 2) Revision: 01.02.2023

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: ALPOMASTIC Härter 519 normal
- 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Hardening agent/ Curing agent
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

FEYCOLOR GmbH Maxhüttenstraße 6 93055 Regensburg Germany

Tel.: +49 (0) 941-60497-0 Fax: +49 (0) 941-60497-30

info@feycolor.com www.feycolor.com

Office hours:

Monday - Thursday: 08:00 - 12:00 und 13:00 - 16:00

Friday: 08:00 - 12:00

Email: sd@feycolor.com www.feycolor.com

• 1.4 Emergency telephone number: +49 (0) 700 24 11 21 12 (FCM)

#### **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)





according to 1907/2006/EC, Article 31

Printing date 01.02.2023 Version number 3 (replaces version 2) Revision: 01.02.2023

Trade name: ALPOMASTIC Härter 519 normal

(Contd. of page 1)

#### · Hazard pictograms







GHS02 GHS05 GHS07

## · Signal word Danger

#### · Hazard-determining components of labelling:

3-aminomethyl-3,5,5-trimethylcyclohexylamine

Phenol, methylstyrenated

m-phenylenebis(methylamine)

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine)

#### · Hazard statements

H226 Flammable liquid and vapour.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

#### **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or

shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

#### · 2.3 Other hazards

### · Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

#### **SECTION 3: Composition/information on ingredients**

## · 3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

## Dangerous components:

CAS: 68512-30-1 Phenol, methylstyrenated Skin Irrit. 2. H315: Skin Irrit. 3. H315: Skin Irrit

≥10-<25%

Reg.nr.: 01-2119555274-38

🕩 Skin Irrit. 2, H315; Skin Sens. 1B, H317; Aquatic Chronic 3, H412

(Contd. on page 3)





according to 1907/2006/EC, Article 31

Printing date 01.02.2023 Version number 3 (replaces version 2) Revision: 01.02.2023

Trade name: ALPOMASTIC Härter 519 normal

CAS: 100-51-6	Benzyl alcohol	ontd. of pag 2.5-<10
EINECS: 202-859-9 Reg.nr.: 01-2119492630-38	(1) Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319	
CAS: 2855-13-2 EINECS: 220-666-8 Reg.nr.: 01-2119514687-32	3-aminomethyl-3,5,5-trimethylcyclohexylamine  Skin Corr. 1B, H314; Eye Dam. 1, H318; ♠ Acute Tox. 4, H302; Skin Sens. 1A, H317  ATE: LD50 oral: 1,030 mg/kg  Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.001 %	≥5-<10
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	Xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	5-<109
CAS: 113930-69-1 NLP: 500-302-7 Reg.nr.: 01-2119965162-39	4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine)  Aquatic Chronic 2, H411; Acute Tox. 4, H302; Skin Sens. 1, H317	2.5-<10
CAS: 1477-55-0 EINECS: 216-032-5 Reg.nr.: 01-2119480150-50	m-phenylenebis(methylamine) Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥1-<2.5
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35	Ethylbenzene  Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Aquatic Chronic 3, H412	<2.5%
CAS: 69-72-7 EINECS: 200-712-3	salicylic acid ❖ Repr. 2, H361d; ❖ Eye Dam. 1, H318; ❖ Acute Tox. 4, H302	≥1-<2.5

· Additional information: For the wording of the listed hazard phrases refer to section 16.

#### **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents: Water with full jet

(Contd. on page 4)



Page 4/10

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.02.2023 Version number 3 (replaces version 2) Revision: 01.02.2023

Trade name: ALPOMASTIC Härter 519 normal

(Contd. of page 3)

#### 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

## **SECTION 6: Accidental release measures**

#### · 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

#### 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

#### · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

#### · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

### · 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

### Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

#### · 7.2 Conditions for safe storage, including any incompatibilities

- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

### **SECTION 8: Exposure controls/personal protection**

#### · 8.1 Control parameters

#### · Ingredients with limit values that require monitoring at the workplace:

## 1330-20-7 Xylene

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm

Sk; BMGV

(Contd. on page 5)





according to 1907/2006/EC, Article 31

Printing date 01.02.2023 Version number 3 (replaces version 2) Revision: 01.02.2023

Trade name: ALPOMASTIC Härter 519 normal

(Contd. of page 4)

#### 100-41-4 Ethylbenzene

WEL Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm

Sk

#### · Ingredients with biological limit values:

#### 1330-20-7 Xylene

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift Parameter: methyl hippuric acid

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see item 7.
- Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

## · Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

GB





according to 1907/2006/EC, Article 31

Printing date 01.02.2023 Version number 3 (replaces version 2) Revision: 01.02.2023

Trade name: ALPOMASTIC Härter 519 normal

(Contd. of page 5)

## **SECTION 9: Physical and chemical properties**

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Fluid

· Colour: According to product specification

Odour: Characteristic
Odour threshold: Not determined.

• Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling

range 137-143 °C (1330-20-7 Xylene)

· Flammability Flammable.

· Lower and upper explosion limit

Lower: Not determined.Upper: Not determined.

· Flash point: 23 °C (DIN EN ISO 1523:2002)

Ignition temperature:
 Decomposition temperature:
 pH
 435 °C (DIN 51794)
 Not determined.
 Not determined.

· Viscosity:

· Kinematic viscosity at 20 °C 145 s (DIN 53211/4) Dynamic: Not determined.

·Solubility

• water: Not miscible or difficult to mix.

• Partition coefficient n-octanol/water (log value) Not determined. • Vapour pressure at 20 °C: 6.7-8.2 hPa

Density and/or relative density

Density at 20 °C: 1.468 g/cm³ (DIN EN ISO 2811-1)

Relative densityVapour densityNot determined.Not determined.

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health and

environment, and on safety.

· **Auto-ignition temperature:** Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of explosive

air/vapour mixtures are possible.

· Solvent content:

· VOC (EC) 7.50 % · Solids content (weight-%): 92.5 %

· Change in condition

· Evaporation rate Not determined.

· Information with regard to physical hazard classes

Explosives
Flammable gases
Aerosols
Oxidising gases
Gases under pressure
Void
Void

· Flammable liquids Flammable liquid and vapour.

(Contd. on page 7)





according to 1907/2006/EC, Article 31

Printing date 01.02.2023 Version number 3 (replaces version 2) Revision: 01.02.2023

Trade name: ALPOMASTIC Härter 519 normal

		(Contd. of page 6)
· Flammable solids	Void	
· Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit flamm	able	
gases in contact with water	Void	
· Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
· Desensitised explosives	Void	

## **SECTION 10: Stability and reactivity**

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

### **SECTION 11: Toxicological information**

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Skin corrosion/irritation Causes severe skin burns and eye damage.
- Serious eye damage/irritation Causes serious eye damage.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- · 11.2 Information on other hazards

· Endocrine	disrupting properties	
68512-30-1	Phenol, methylstyrenated	List II
69-72-7	salicylic acid	List II, III

#### **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · **vPvB:** Not applicable.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.

(Contd. on page 8)





according to 1907/2006/EC, Article 31

Printing date 01.02.2023 Version number 3 (replaces version 2) Revision: 01.02.2023

Trade name: ALPOMASTIC Härter 519 normal

(Contd. of page 7)

- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

## **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

14.1 UN number or ID number	
ADR, IMDG, IATA	UN2734
14.2 UN proper shipping name	
ADR	UN2734 AMINES, LIQUID, CORROSIVE, FLAMMABLE
	N.O.S. (ISOPHORONEDIAMINE, XYLENES)
IMDG, IATA	AMINES, LIQUID, CORROSIVE, FLAMMABLE, N.O.S
	(ISOPHORONEDIAMINE, XYLENES)

· ADR





· Class 8 (CF1) Corrosive substances.

· Label 8+3

· IMDG





· Class 8 Corrosive substances.

(Contd. on page 9)





according to 1907/2006/EC, Article 31

Printing date 01.02.2023 Version number 3 (replaces version 2) Revision: 01.02.2023

Trade name: ALPOMASTIC Härter 519 normal

	(Contd. of page
Label	8/3
IATA	
Class	8 Corrosive substances.
Label	8 (3)
14.4 Packing group	
ADR, IMDG, IATA	II
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Warning: Corrosive substances.
Hazard identification number (Kemler code):	83
EMS Number:	F-E,S-C
Segregation groups Stowage Category	(SGG18) Alkalis A
Segregation Code	SG35 Stow "separated from" SGG1-acids
14.7 Maritime transport in bulk according to IM	
instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Transport category	2
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	1L
UN "Model Regulation":	UN 2734 AMINES, LIQUID, CORROSIVE, FLAMMABL N.O.S. (ISOPHORONEDIAMINE, XYLENES), 8 (3), II

## **SECTION 15: Regulatory information**

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · National regulations:
- Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %
NK	2.5-<10

(Contd. on page 10)





according to 1907/2006/EC, Article 31

Printing date 01.02.2023 Version number 3 (replaces version 2) Revision: 01.02.2023

Trade name: ALPOMASTIC Härter 519 normal

(Contd. of page 9)

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H361d Suspected of damaging the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

#### Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

#### Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity – Category 4 Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation - Category 1

Skin Sens. 1A: Skin sensitisation - Category 1A

Skin Sens. 1B: Skin sensitisation – Category 1B

Repr. 2: Reproductive toxicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

\* Data compared to the previous version altered.