

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 4 (replaces version 3)

Revision: 01.02.2023

| SECTION 1: Identification of the substance/mixture and of the company/undertaking |
|--|
| · 1.1 Product identifier |
| Trade name: FEYCOTECT Härter 509 1.2 Relevant identified uses of the substance or mixture and uses advised against Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) Product category PC9a Coatings and paints, thinners, paint removers Application of the substance / the mixture Hardening agent/ Curing agent |
| • 1.3 Details of the supplier of the safety data sheet • Manufacturer/Supplier: FEYCOLOR GmbH Maxhüttenstraße 6 93055 Regensburg Germany |
| Tel.: +49 (0) 941-60497-0 Fax: +49 (0) 941-60497-30 info@feycolor.com_www.feycolor.com |
| Office hours: Monday - Thursday: 08:00 - 12:00 und 13:00 - 16:00 Friday: 08:00 - 12:00 |
| Email: sd@feycolor.com www.feycolor.com · 1.4 Emergency telephone number: +49 (0) 700 24 11 21 12 (FCM) |
| SECTION 2: Hazards identification |
| • 2.1 Classification of the substance or mixture • Classification according to Regulation (EC) No 1272/2008 |
| Flam. Liq. 3 H226 Flammable liquid and vapour. |
| health hazard |
| STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure. |
| corrosion |
| Eye Dam. 1 H318 Causes serious eye damage. |
| Skin Irrit. 2 H315 Causes skin irritation. (Contd. on page 2) |



Printing date 01.02.2023

Page 2/11

Safety data sheet

according to 1907/2006/EC, Article 31

Version number 4 (replaces version 3)

Revision: 01.02.2023

Trade name: FEYCOTECT Härter 509

(Contd. of page 1) Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness. · 2.2 Label elements · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation. · Hazard pictograms GHS05 GHS07 GHS02 GHS08 · Signal word Danger · Hazard-determining components of labelling: Isobutanol **Xylene** Bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight 700-1100) Butan-1-ol · Hazard statements Flammable liquid and vapour. H226 H315 Causes skin irritation. H318 Causes serious eye damage. H317 May cause an allergic skin reaction. H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. H373 Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smokina. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 Immediately call a POISON CENTER/doctor. P321 Specific treatment (see on this label). P362+P364 Take off contaminated clothing and wash it before reuse. · Additional information: EUH205 Contains epoxy constituents. May produce an allergic reaction. Restricted to professional users. · 2.3 Other hazards Results of PBT and vPvB assessment · **PBT:** Not applicable. · vPvB: Not applicable.

- **SECTION 3: Composition/information on ingredients**
- · 3.2 Mixtures
- Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 4 (replaces version 3)

Revision: 01.02.2023

Trade name: FEYCOTECT Härter 509

| | (Co | ntd. of page 2 |
|--|--|----------------|
| [.] Dangerous components: | | |
| CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32 | Xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 | 25-50% |
| CAS: 78-83-1 EINECS: 201-148-0 Reg.nr.: 01-2119484609-23 | Isobutanol Flam. Liq. 3, H226; 🔶 Eye Dam. 1, H318; 아 Skin Irrit. 2, H315; STOT SE 3, H335-H336 | 10-25% |
| CAS: 71-36-3 EINECS: 200-751-6 Reg.nr.: 01-2119484630-38 | Butan-1-ol ♦ Flam. Liq. 3, H226; ♦ Eye Dam. 1, H318; ♦ Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336 | 10-25% |
| CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29 | n-Butyl acetate Flam. Liq. 3, H226; | 5-<10% |
| CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35 | Ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Aquatic Chronic 3, H412 | 2.5-<10% |
| CAS: 25068-38-6 | Bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight 700-1100) Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205 | ≥1-<2.5% |

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation:
- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- $^{\circ}$ 5.2 Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- 5.3 Advice for firefighters
- Protective equipment: Mouth respiratory protective device.

(Contd. on page 4)



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 4 (replaces version 3)

Revision: 01.02.2023

(Contd. of page 3)

Trade name: FEYCOTECT Härter 509

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent.

Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

- · 6.4 Reference to other sections
- See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles: No special requirements.

- Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Keep container tightly sealed.

· Storage class: 3

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

| Ingredients with limit values that require monitoring at the workplace: | | | |
|---|--|--|--|
| 1330- | 20-7 Xylene | | |
| | Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV | | |
| 78-83 | -1 Isobutanol | | |
| WEL | Short-term value: 231 mg/m³, 75 ppm Long-term value: 154 mg/m³, 50 ppm | | |
| 71-36 | -3 Butan-1-ol | | |
| | Short-term value: 154 mg/m³, 50 ppm Sk | | |
| | (Contd. on page 5) | | |

Page 4/11



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 4 (replaces version 3)

Revision: 01.02.2023

Trade name: FEYCOTECT Härter 509

| 123-00-4 11-0 | Butyl acetate | (Contd. of pa |
|---|---|---------------|
| | erm value: 966 mg/m³, 200 ppm | |
| | erm value: 724 mg/m³, 150 ppm | |
| 100-41-4 Eth | ylbenzene | |
| WEL Short-te | erm value: 552 mg/m³, 125 ppm | |
| Long-te | erm value: 441 mg/m³, 100 ppm | |
| Sk | | |
| Ingredients | with biological limit values: | |
| 1330-20-7 Xy | /lene | |
| BMGV 650 n | nmol/mol creatinine | |
| Mediu | um: urine | |
| Samp | pling time: post shift | |
| Parar | meter: methyl hippuric acid | |
| | nformation: The lists valid during the making were used as basis. | |
| Additional in | | |
| | | |
| 8.2 Exposure | e controls | |
| 8.2 Exposure Appropriate | e controls engineering controls No further data; see item 7. | |
| 8.2 Exposure Appropriate Individual pr | e controls engineering controls No further data; see item 7. rotection measures, such as personal protective equipment | |
| 8.2 Exposure Appropriate Individual pr General prot | e controls engineering controls No further data; see item 7. rotection measures, such as personal protective equipment tective and hygienic measures: | |
| 8.2 Exposure Appropriate Individual pr General prot | e controls engineering controls No further data; see item 7. rotection measures, such as personal protective equipment | |
| 8.2 Exposure Appropriate Individual pr General prot Keep away fre | e controls engineering controls No further data; see item 7. rotection measures, such as personal protective equipment tective and hygienic measures: | |
| 8.2 Exposure Appropriate Individual pr General prot Keep away fr Immediately | e controls engineering controls No further data; see item 7. rotection measures, such as personal protective equipment tective and hygienic measures: rom foodstuffs, beverages and feed. | |
| 8.2 Exposure Appropriate Individual prof General prof Keep away fr Immediately r Wash hands | e controls engineering controls No further data; see item 7. rotection measures, such as personal protective equipment tective and hygienic measures: rom foodstuffs, beverages and feed. remove all soiled and contaminated clothing before breaks and at the end of work. | |
| 8.2 Exposure Appropriate Individual prof General prof Keep away fr Immediately r Wash hands Store protecti | e controls engineering controls No further data; see item 7. rotection measures, such as personal protective equipment tective and hygienic measures: rom foodstuffs, beverages and feed. remove all soiled and contaminated clothing before breaks and at the end of work. ive clothing separately. | |
| 8.2 Exposure Appropriate Individual prof General prof Keep away fro Immediately r Wash hands Store protection Avoid contact | e controls engineering controls No further data; see item 7. rotection measures, such as personal protective equipment tective and hygienic measures: rom foodstuffs, beverages and feed. remove all soiled and contaminated clothing before breaks and at the end of work. | |

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)



Safety data sheet according to 1907/2006/EC, Article 31


Printing date 01.02.2023

Version number 4 (replaces version 3)

Revision: 01.02.2023

(Contd. of page 5)

Trade name: FEYCOTECT Härter 509



Tightly sealed goggles

| SECTION 9: Physical and chemical propertie | S |
|--|---|
| • 9.1 Information on basic physical and chemical p | roperties |
| General Information | |
| Physical state | Fluid |
| Colour: | According to product specification |
| Odour: | Characteristic |
| Odour threshold: | Not determined. |
| Melting point/freezing point: | Undetermined. |
| Boiling point or initial boiling point and boiling | |
| range | 108 °C (78-83-1 Isobutanol) |
| Flammability | Flammable. |
| Lower and upper explosion limit | |
| Lower: | 1.1 Vol % (1330-20-7 Xylene) |
| Upper: | 12 Vol % (78-83-1 Isobutanol) |
| Flash point: | 24 °C (DIN EN ISO 1523:2002, 1330-20-7 Xylene) |
| Ignition temperature: | 340 °C (DIN 51794, 71-36-3 Butan-1-ol) |
| Decomposition temperature: | Not determined. |
| рН | Not determined. |
| Viscosity: | |
| Kinematic viscosity | Not determined. |
| Dynamic at 20 °C: | 3,500 mPas |
| Solubility | |
| water: | Not miscible or difficult to mix. |
| Partition coefficient n-octanol/water (log value) | Not determined. |
| Vapour pressure at 20 °C: | 12 hPa (78-83-1 Isobutanol) |
| Density and/or relative density | |
| Density at 20 °C: | 0.926 g/cm ³ (DIN EN ISO 2811-1) |
| Relative density | Not determined. |
| Vapour density | Not determined. |
| 9.2 Other information | |
| Appearance: | |
| Form: | Fluid |
| Important information on protection of health an | |
| environment, and on safety. | |
| Auto-ignition temperature: | Product is not selfigniting. |
| Explosive properties: | Product is not explosive. However, formation of explosivair/vapour mixtures are possible. |
| Solvent content: | · · |
| VOC (EC) | 67.50 % |
| Solids content (weight-%): | 32.5 % |
| | (Contd. on page |
| | |



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 4 (replaces version 3)

Revision: 01.02.2023

Trade name: FEYCOTECT Härter 509

| | | (Contd. of page |
|--|------------------------------|-----------------|
| Change in condition | | |
| Evaporation rate | Not determined. | |
| Information with regard to physical hazard c | lasses | |
| Explosives | Void | |
| Flammable gases | Void | |
| Aerosols | Void | |
| Oxidising gases | Void | |
| Gases under pressure | Void | |
| Flammable liquids | Flammable liquid and vapour. | |
| Flammable solids | Void | |
| Self-reactive substances and mixtures | Void | |
| Pyrophoric liquids | Void | |
| Pyrophoric solids | Void | |
| Self-heating substances and mixtures | Void | |
| Substances and mixtures, which emit flamm | able | |
| gases in contact with water | Void | |
| Oxidising liquids | Void | |
| Oxidising solids | Void | |
| Organic peroxides | Void | |
| Corrosive to metals | Void | |
| Desensitised explosives | Void | |

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

· Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products:

Possible in traces. Nitrogen oxides Hydrogen chloride (HCI) Carbon monoxide Nitrogen oxides (NOx)

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

• Acute toxicity Based on available data, the classification criteria are not met.

| · LD/LC50 values relevant for classification: | | | |
|---|---|-----------------------|--|
| 1330-20-7 | Xylene | | |
| Oral | LD50 | 5,251 mg/kg (rat) | |
| Dermal | LD50 | >5,000 mg/kg (rabbit) | |
| Inhalative | LC50/4 h | 29 mg/l (rat) | |
| · Skin corro | Skin corrosion/irritation Causes skin irritation. | | |

(Contd. on page 8)

[–] GB



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 4 (replaces version 3)

Revision: 01.02.2023

(Contd. of page 7)

Trade name: FEYCOTECT Härter 509

- · Serious eye damage/irritation Causes serious eye damage.
- Respiratory or skin sensitisation May cause an allergic skin reaction.
- STOT-single exposure May cause respiratory irritation. May cause drowsiness or dizziness.
- STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.
- · 11.2 Information on other hazards
- Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) : hazardous for water Do not allow product to reach ground water, water course or sewage system. Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

| 14.1 UN number or ID number | | |
|------------------------------|-------------------------------|--|
| ADR, IMDG, IATA | UN1263 | |
| 14.2 UN proper shipping name | | |
| ADR | UN1263 PAINT RELATED MATERIAL | |
| IMDG, IATA | PAINT RELATED MATERIAL | |

Page 8/11



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 4 (replaces version 3)

Revision: 01.02.2023

Trade name: FEYCOTECT Härter 509

| | (Contd. of page |
|---|---|
| · 14.3 Transport hazard class(es) | |
| · ADR | |
| | |
| · Class | 3 (F1) Flammable liquids. |
| ·Label | 3 |
| · IMDG, IATA | |
| · Class | 3 Flammable liquids. |
| Label | 3 |
| 14.4 Packing group | |
| · ADR, IMDG, IATA | III |
| · 14.5 Environmental hazards: | Not applicable. |
| 14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category | Warning: Flammable liquids. 30 F-E, <u>S-E</u> A |
| · 14.7 Maritime transport in bulk according to IM | 0 |
| instruments | Not applicable. |
| · Transport/Additional information: | |
| ADR Limited quantities (LQ) Transport category Tunnel restriction code Remarks: | 5L 3 D/E ≤ 450 l: 2.2.3.1.5 ADR |
| IMDG Limited quantities (LQ) Remarks: | 5L ≤ 450 I: 2.3.2.5 IMDG |
| · UN "Model Regulation": | UN 1263 PAINT RELATED MATERIAL, 3, III |

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

• Seveso category P5c FLAMMABLE LIQUIDS

· Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

(Contd. on page 10)

Page 9/11



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 4 (replaces version 3)

Revision: 01.02.2023

(Contd. of page 9)

Trade name: FEYCOTECT Härter 509

| Qualifying quantit | y (tonnes) for the | e application of u | upper-tier requiremer | 1ts 50,000 t |
|--------------------|--------------------|--------------------|-----------------------|---------------------|
|--------------------|--------------------|--------------------|-----------------------|---------------------|

· National regulations:

Additional classification according to Decree on Hazardous Materials, Annex II:

| Class | Share in % |
|-------|------------|
| NK | 50-100 |

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- Highly flammable liquid and vapour. H225
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- May cause an allergic skin reaction. H317
- Causes serious eye damage. H318
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- May cause drowsiness or dizziness. H336
- H373 May cause damage to organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.
- EUH205 Contains epoxy constituents. May produce an allergic reaction.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 2: Flammable liquids Category 2 Flam. Liq. 3: Flammable liquids Category 3
- Acute Tox. 4: Acute toxicity Category 4
- Skin Irrit. 2: Skin corrosion/irritation Category 2
- Eye Dam. 1: Serious eye damage/eye irritation Category 1 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2
- Skin Sens. 1: Skin sensitisation Category 1
- STOT SE 3: Specific target organ toxicity (single exposure) Category 3
- STOT RE 2: Specific target organ toxicity (repeated exposure) Category 2
- Asp. Tox. 1: Aspiration hazard Category 1

(Contd. on page 11)

GB

Page 10/11



Page 11/11

Safety data sheet according to 1907/2006/EC, Article 31

Revision: 01.02.2023

Printing date 01.02.2023

Version number 4 (replaces version 3)

Trade name: FEYCOTECT Härter 509

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3 • * Data compared to the previous version altered.

(Contd. of page 10)