

Article No.: 1-1520 RELAFLOOR 1520 2K EP WV
Print date: 31.07.2017 Revision date: 13.07.2017 999998 EN
Version: 1.5 Issue date: 13.07.2017 Page 1 / 6

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. product identifiers

Article No. (manufacturer/supplier) 1-1520
Identification of the substance or mixture RELAFLOOR 1520 2K EP WV
Grundierung farblos
MV-GEW: 3:1 mit Komponente B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Floor Coating

1.3. Details to the supplier providing the material safety data sheet

Producer:

FEYCOLOR GmbH
Maxhuettenstraße 6,
93055 Regensburg,
Germany

Tel.: +49 (0) 941/ 60497-0
Fax.: +49 (0) 941/ 60497-30
info@feycolor.com
www.feycolor.com

Email: sd@feycolor.com

1.4. Emergency telephone number: +49 (0) 700 24 11 21 12 (FCM)

Austrian Poisons Information Center: +43 (0) 1406 4343

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Eye Dam. 1 / H318 Serious eye damage/eye irritation Causes serious eye damage.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Danger

Hazard statements

H318 Causes serious eye damage.

Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/attention.

contains:

Triethylentetramin

Supplemental Hazard information (EU)

not applicable

2.3. Other hazards

SECTION 3: Composition / information on ingredients

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010

FEYCOLOR®

Article No.: 1-1520 RELAFLOOR 1520 2K EP WV
Print date: 31.07.2017 Revision date: 13.07.2017
Version: 1.5 Issue date: 13.07.2017

999998 EN
Page 2 / 6

3.2. Mixtures

Product description / chemical characterization

Description Zubereitung aus Bindemittel, Pigment,
Füllstoff, Additiven und Wasser

Hazardous ingredients

Classification according to Regulation (EC) No 1272/2008 [CLP]

EC No.	REACH No.	Wt %
CAS No.	Chemical name	Remark
INDEX No.	classification	
1311389-92-0	Triethylentetramin Eye Dam. 1 H318	25 - 50

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Extinguishing media which must not be used for safety reasons:

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Special protective equipment for firefighters

Provide a conveniently located respiratory protective device.

Additional information

Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ventilate affected area. Do not breathe vapours. See protective measures under point 7 and 8.

6.2. Environmental precautions

Article No.:	1-1520	RELAFLOOR 1520 2K EP WV	
Print date:	31.07.2017	Revision date: 13.07.2017	999998 EN
Version:	1.5	Issue date: 13.07.2017	Page 3 / 6

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see chapter 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid contact with skin, eyes and clothes. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRBS 2153)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values:

INDEX No. not applicable / CAS No.

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Occupational exposure controls

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time (maximum wearing time) > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles DIN EN 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye protection

Wear closely fitting protective glasses in case of splashes.

Protective clothing

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Article No.: 1-1520
Print date: 31.07.2017
Version: 1.5

RELAFLOOR 1520 2K EP WV
Revision date: 13.07.2017
Issue date: 13.07.2017

999998 EN
Page 4 / 6

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:

Physical state liquid
Colour siehe Artikelbezeichnung
Odour characteristic

Safety relevant basis data

	Unit	Method	Remark
Flash point (°C):	not applicable °C		
Ignition temperature in °C:	not applicable °C		
Lower explosion limit:	1,7 Vol-%		
Upper explosion limit:	13,1 Vol-%		
Vapour pressure at 20 °C: 20	0,1705 hPa		
Density at 20 °C: 20	1,00 g/cm ³		
Water solubility (g/L):	partially soluble		
pH at 20 °C: 20	n.a.		
Viscosity at 20 °C: 20	> 160 s 4 mm	DIN 53211	
Solvent separation test (%):	< 3 %		
Solid content (%):	34 Wt %		
solvent content:			
Organic solvents:	1,69 Wt %		
Water:	64,07 Wt %		

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to chapter 7.

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. Conditions to avoid

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to chapter 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

Classification according to Regulation (EC) No 1272/2008 [CLP]
No data on preparation itself available.

11.1. Information on toxicological effects

Acute toxicity

Toxicological data are not available.

skin corrosion/irritation; Serious eye damage/eye irritation

Toxicological data are not available.

Respiratory or skin sensitisation

Toxicological data are not available.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Toxicological data are not available.

Article No.: 1-1520 RELAFLOOR 1520 2K EP WV
Print date: 31.07.2017 Revision date: 13.07.2017
Version: 1.5 Issue date: 13.07.2017

999998 EN
Page 5 / 6

Specific target organ toxicity

Toxicological data are not available.

Aspiration hazard

Toxicological data are not available.

Practical experience/human evidence

Other observations:

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall Assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

Remark

There is no information available on the preparation itself .

SECTION 12: Ecological information

overall evaluation

Classification according to Regulation (EC) No 1272/2008 [CLP]

There is no information available on the preparation itself .

Do not allow to enter into surface water or drains.

12.1. Toxicity

No information available.

Long-term Ecotoxicity

Toxicological data are not available.

12.2. Persistence and degradability

Toxicological data are not available.

12.3. Bioaccumulative potential

Toxicological data are not available.

Bioconcentration factor (BCF)

Toxicological data are not available.

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product

Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

080111 waste paint and varnish containing organic solvents or other dangerous substances

packaging

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

This mixture is not classified as dangerous according to international transport regulations (ADR/RID, IMDG, ICAO/IATA).

No dangerous good in sense of this transport regulation.

14.1. UN number

not applicable

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010

FEYCOLOR®

Article No.: 1-1520 RELAFLOOR 1520 2K EP WV
Print date: 31.07.2017 Revision date: 13.07.2017 999998 EN
Version: 1.5 Issue date: 13.07.2017 Page 6 / 6

14.2. **UN proper shipping name**

14.3. **Transport hazard class(es)**

not applicable

14.4. **Packing group**

not applicable

14.5. **Environmental hazards**

Land transport (ADR/RID)

not applicable

Marine pollutant

not applicable

14.6. **Special precautions for user**

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

Further information

Land transport (ADR/RID)

tunnel restriction code

-

Sea transport (IMDG)

EmS-No.

not applicable

14.7. **Transport in bulk according to Annex II of Marpol and the IBC Code**

not applicable

SECTION 15: Regulatory information

15.1. **Safety, health and environmental regulations/legislation specific for the substance or mixture**

EU legislation

Information according to 1999/13/EC about limitation of emissions of volatile organic compounds (VOC-guideline).

VOC-value (in g/L) ISO 11890-2: 17

VOC-value (in g/L) ASTM D 2369: 47

according to EU-regulation 2004/42/EC (appendix II)

EU limit value for this product (cat. (Cat. A/j)): 140 g/l (2007)/140 g/l (2010).

This product contains max 13 g/l VOC.

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Other regulations, restrictions and prohibition regulations

15.2. **Chemical Safety Assessment**

Chemical safety assessments for substances in this preparation were not carried out.

SECTION 16: Other information

Carbides.:

Eye Dam. 1 / H318

Serious eye damage/eye irritation

Causes serious eye damage.