

according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 01.02.2023

Page 1/11

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### · 1.1 Product identifier

- · Trade name: FEYALKYD 303 Plasto-Coat
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- No further relevant information available.
- · Application of the substance / the mixture Paint
- · 1.3 Details of the supplier of the safety data sheet

• Manufacturer/Supplier: FEYCOLOR GmbH Maxhüttenstraße 6 93055 Regensburg Germany

Tel.: +49 (0) 941-60497-0 Fax: +49 (0) 941-60497-30 info@feycolor.com www.feycolor.com

Office hours: Monday - Thursday: 08:00 - 12:00 und 13:00 - 16:00 Friday: 08:00 - 12:00

Email: sd@feycolor.com www.feycolor.com

· 1.4 Emergency telephone number: +49 (0) 700 24 11 21 12 (FCM)

#### **SECTION 2: Hazards identification**

2.1 Classification of the substance or mixture
 Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.

health hazard

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Corrosion

Eye Dam. 1 H318 Causes serious eye damage.



Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 2)

GB



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 01.02.2023

Trade name: FEYALKYD 303 Plasto-Coat



#### **SECTION 3: Composition/information on ingredients**

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 01.02.2023

Trade name: FEYALKYD 303 Plasto-Coat

Dangerous components:	,	
CAS: 64742-95-6 EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Hydrocarbons, C9, aromatics ♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411; ♦ STOT SE 3, H335-H336, EUH066	≥2.5-<15%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	Xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	≥10-<15%
CAS: 7779-90-0 EINECS: 231-944-3 Reg.nr.: 01-2119485044-40	Trizinc bis(orthophosphate) Aquatic Acute 1, H400; Aquatic Chronic 1, H410	2.5-<10%
CAS: 78-83-1 EINECS: 201-148-0 Reg.nr.: 01-2119484609-23	Isobutanol ♦ Flam. Liq. 3, H226; ♦ Eye Dam. 1, H318; ♦ Skin Irrit. 2, H315; STOT SE 3, H335-H336	≥3-<10%
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35	Ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Aquatic Chronic 3, H412	<2.5%
EC number: 919-857-5 Reg.nr.: 01-2119463258-33	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics Flam. Liq. 3, H226;  Asp. Tox. 1, H304;  STOT SE 3, H336, EUH066	<2.5%
CAS: 2457-01-4 EINECS: 219-535-8	barium bis(2-ethylhexanoate) ♦ Repr. 2, H361d; ♦ Eye Dam. 1, H318; ♦ Acute Tox. 4, H302; Acute Tox. 4, H332	<1%
CAS: 136-52-7 EINECS: 205-250-6 Reg.nr.: 01-2119524678-29	cobalt bis(2-ethylhexanoate) Repr. 1B, H360Fd; Aquatic Acute 1, H400; Eye Irrit. 2, H319; Skin Sens. 1A, H317; Aquatic Chronic 3, H412	<0.1%

#### **SECTION 4: First aid measures**

· 4.1 Description of first aid measures

· General information: Immediately remove any clothing soiled by the product.

• After inhalation: Supply fresh air; consult doctor in case of complaints.

• After skin contact: Immediately rinse with water.

• After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

• After swallowing: If symptoms persist consult doctor.

• 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

#### **SECTION 5: Firefighting measures**

· 5.1 Extinguishing media

• Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

• For safety reasons unsuitable extinguishing agents: Water with full jet

(Contd. on page 4)

GB

Page 3/11



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 01.02.2023

Trade name: FEYALKYD 303 Plasto-Coat

- · 5.2 Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

#### **SECTION 6: Accidental release measures**

6.1 Personal precautions, protective equipment and emergency procedures Mount respiratory protective device. Wear protective equipment. Keep unprotected persons away.
6.2 Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent. Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### **SECTION 7: Handling and storage**

7.1 Precautions for safe handling
 Ensure good ventilation/exhaustion at the workplace.

 Prevent formation of aerosols.
 Information about fire - and explosion protection:
 Keep ignition sources away - Do not smoke.

 Protect against electrostatic charges.

- Keep respiratory protective device available.
- · 7.2 Conditions for safe storage, including any incompatibilities · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

#### · 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

## 1330-20-7 Xylene

WEL Short-term value: 441 mg/m<sup>3</sup>, 100 ppm Long-term value: 220 mg/m<sup>3</sup>, 50 ppm

#### Sk; BMGV

GB

(Contd. of page 3)

Page 4/11



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 01.02.2023

Trade name: FEYALKYD 303 Plasto-Coat

	(Contd. of page 4
78-83	3-1 Isobutanol
WEL	Short-term value: 231 mg/m³, 75 ppm
	Long-term value: 154 mg/m³, 50 ppm
100-4	1-4 Ethylbenzene
WEL	Short-term value: 552 mg/m³, 125 ppm
	Long-term value: 441 mg/m <sup>3</sup> , 100 ppm
	Sk
136-5	2-7 cobalt bis(2-ethylhexanoate)
WEL	Long-term value: 0.1 mg/m <sup>3</sup>
	as Co; Carc, Sen
· Ingre	dients with biological limit values:
1330	-20-7 Xylene
BMG	V 650 mmol/mol creatinine
	Medium: urine
	Sampling time: post shift
	Parameter: methyl hippuric acid
· Addi	tional information: The lists valid during the making were used as basis.
· 82F	xposure controls
	opriate engineering controls No further data; see item 7.
	idual protection measures, such as personal protective equipment
	eral protective and hygienic measures:
	a protocol for a la right because and for d

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes. Avoid contact with the eyes and skin.

#### Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

#### · Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

Page 5/11



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 01.02.2023

(Contd. of page 5)

Trade name: FEYALKYD 303 Plasto-Coat



Tightly sealed goggles

9.1 Information on basic physical and chemical properties         General Information         Physical state       Fluid         Colour:       According to product specification         Odour threshold:       Not determined.         Melting point/freezing point:       Undetermined.         Boiling point or initial boiling point and boiling range       137-143 °C (1330-20-7 Xylene)         Flammability       Flammable.         Lower and upper explosion limit       0.7 Vol % (64742-95-6 Hydrocarbons, C9, aromatics)         Upper:       7.5 Vol % (64742-95-6 Hydrocarbons, C9, aromatics)         Plash point:       24 °C (DIN EN ISO 1523:2002)         Decomposition temperature:       Not determined.         PH       Not determined.         Viscosity:       Solubility         Viscosity:       Viscosity:         Kinematic viscosity at 20 °C       >95 s (DIN 53211/4)         Dynamic:       Not determined.         Solubility       Not determined.         Water:       Partition coefficient n-octanol/water (log value)         Pensity and/or relative density       Not determined.         Ponesity and/or relative density       Not determined.         Vapour density       Not determined.         9.2 Other information on protection of health and environment,	SECTION 9: Physical and chemical propertie	S
General InformationPhysical stateFluidColour:According to product specificationOdour threshold:Not determined.Metting point/freezing point:Undetermined.Boiling point or initial boiling point and boiling range137-143 °C (1330-20-7 Xylene)FlammabilityFlammabile.Lower:0.7 Vol % (64742-95-6 Hydrocarbons, C9, aromatics)Upper:7.5 Vol % (64742-95-6 Hydrocarbons, C9, aromatics)Plans point:24 °C (DIN EN ISO 1523:2002)Decomposition temperature:Not determined.pHNot determined.Viscosity:Viscosity:Kinematic viscosity at 20 °C>95 s (DIN 53211/4)Dynamic:Not determined.SolubilityNot determined.Vapour pressure at 20 °C:.95 s (DIN 53211/4)Density and/or relative densityNot determined.Partition coefficient n-octanol/water (log value)Not determined.Vapour pressure at 20 °C:1.361 g/cm³ (DIN EN ISO 2811-1)Relative densityNot determined.Vapour densityNot determined.9.2 Other information on protection of health and environment, and on safety.Product is not selfigniting.Form:FluidFourie:Product is not selfigniting.Solvent content:Product is not selfigniting.VOC (EC)33.31 %Solidis content (weight-%):66.7 %Change in conditionFluidEvaporation rateNot determined.	• 9.1 Information on basic physical and chemical pi	roperties
Physical stateFluidColour:According to product specificationOdour threshold:Not determined.Odour threshold:Not determined.Bolling point or initial boiling point and boiling range137-143 °C (1330-20-7 Xylene)FlamabilityFlammabile.Lower and upper explosion limit0.7 Vol % (64742-95-6 Hydrocarbons, C9, aromatics)Upper:0.7 Vol % (64742-95-6 Hydrocarbons, C9, aromatics)Flash point:24 °C (DIN EN ISO 1523:2002)Decomposition temperature:Not determined.PHNot determined.Viscosity:95 s (DIN 53211/4)Vord determined.95 s (DIN 53211/4)Dypamic:Not determined.SolubilityNot determined.water:Not miscible or difficult to mix.Partition coefficient n-octanol/water (log value)Not determined.Vapour pressure at 20 °C:1.361 g/cm³ (DIN EN ISO 2811-1)Density and/or relative densityNot determined.Vapour densityNot determined.92. Other informationFluidAuto-ignition temperature:Product is not selfigniting.Form:FluidImportant information on protection of health and environment, and on safety.Product is not selfigniting.Auto-ignition temperature:Product is not selfigniting.Explosive properlies:Product is not selfigniting.Explosive properlies:Product is not selfigniting.Colour constiteFluidMot determined.Product is not selfigniting.Colour constite<		•
Colour:According to product specificationOdour threshold:Not determined.Metting point/freezing point:Undetermined.Boiling point or initial boiling point and boiling range137-143 °C (1330-20-7 Xylene)FlammabilityFlammable.Lower and upper explosion limitFlammable.Lower and upper explosion limit0.7 Vol % (64742-95-6 Hydrocarbons, C9, aromatics)Upper:7.5 Vol % (64742-95-6 Hydrocarbons, C9, aromatics)Plash point:24 °C (DIN EN ISO 1523:2002)Decomposition temperature:Not determined.PHNot determined.Viscosity:Not determined.Kinematic viscosity at 20 °C>95 s (DIN 53211/4)Paymic:Not determined.SolubilityNot determined.Vapour pressure at 20 °C:6.7-8.2 hPa (1330-20-7 Xylene)Density and/or relative densityNot determined.Vapour pressure at 20 °C:1.361 g/cm³ (DIN EN ISO 2811-1)Pelative densityNot determined.92 Other informationFluidAppearance:FluidForm:FluidImportant information on protection of health and environment, and on safety.Auto-ignition temperature:Product is not selfigniting.Product is not selfigniting.Product is not selfigniting.Solvent content:Yroduct is not selfigniting.Vapour densitySolidi content (weight-%):Solvent content:C(EC)Solvent content:Solidi content (weight-%):Color (EC)33.31 %Solids content (wei		Fluid
Odour:CharacteristicOdour threshold:Not determined.Metting point/freezing point:Undetermined.Boiling point or initial boiling point and boiling range137-143 °C (1330-20-7 Xylene)FlammabilityFlammabile.Lower and upper explosion limit0.7 Vol % (64742-95-6 Hydrocarbons, C9, aromatics)Upper:7.5 Vol % (64742-95-6 Hydrocarbons, C9, aromatics)Lower:0.7 Vol % (64742-95-6 Hydrocarbons, C9, aromatics)Upper:7.5 Vol % (64742-95-6 Hydrocarbons, C9, aromatics)Partition temperature:Not determined.PHNot determined.Viscosity:95 s (DIN EN ISO 1523:2002)Wot determined.Viscosity:Viscosity:95 s (DIN 53211/4)Vypamic:Not determined.Solubility95 s (DIN 53211/4)Partition coefficient n-octanol/water (log value)Not determined.Vapour pressure at 20 °C:6.7-8.2 hPa (1330-20-7 Xylene)Density and/or relative densityNot determined.Vapour densityNot determined.Vapour densityNot determined.Vapour densityNot determined.9.2 Other informationFluidAppearance:FluidForm:FluidImportant information on protection of health and environment, and on safety.Auto-lignition temperature:Product is not selfigniting.Explosive properties:Product is not selfigniting.Form:FluidChange in condition6.7 %Change in condition6.7 %	•	According to product specification
Odour threshold:Not determined.Melting point/freezing point:Undetermined.Melting point or initial boiling point and boilingItanmabileFlammabilityFlammable.Lower and upper explosion limitItanmable.Lower and upper explosion limit24 °C (DIN EN ISO 1523:2002)Plant mabilityNot determined.Viscosity:Void (64742-95-6 Hydrocarbons, C9, aromatics)PH24 °C (DIN EN ISO 1523:2002)Decomposition temperature:Not determined.Viscosity:Not determined.Kinematic viscosity at 20 °C>95 s (DIN 53211/4)SolubilityNot determined.Vapour pressure at 20 °C:6.7-8.2 hPa (1330-20-7 Xylene)Density and/or relative densityNot determined.Vapour pressure at 20 °C:6.7-8.2 hPa (1330-20-7 Xylene)Density and/or relative densityNot determined.Vapour pressure at 20 °C:1.361 g/cm <sup>2</sup> (DIN EN ISO 2811-1)Relative densityNot determined.• Vapour densityNot determined.• Vapour densityNot determined.• Vapour densityNot determined.• Solubilion temperature:Product is not selfigniting.• Solubilion temperature:Product is not selfigniting.• Solvent content:Product is not explosive. However, formation of explosive ari/vapour mixtures are possible.• Solvent content:• Product is not explosive. However, formation of explosive.• Solvent content:• Product is not explosive. However, formation of explosive.• Solvent content:• Product is		
Melting point or initial boiling point and boiling rangeUndetermined.Boiling point or initial boiling point and boiling range137.143 °C (1330-20-7 Xylene)FlammabilityFlammable.Lower and upper explosion limit5Lower:0.7 Vol % (64742-95-6 Hydrocarbons, C9, aromatics)Upper:7.5 Vol % (64742-95-6 Hydrocarbons, C9, aromatics)Plash point:24 °C (DIN EN ISO 1523:2002)Decomposition temperature:Not determined.PHNot determined.Viscosity:-Kinematic viscosity at 20 °C>95 s (DIN 53211/4)Dynamic:Not determined.Solubility-water:Not miscible or difficult to mix.Partition coefficient n-octanol/water (log value)Not determined.Vapour pressure at 20 °C:6.7-8.2 hPa (1330-20-7 Xylene)Density at 20 °C:1.361 g/cm³ (DIN EN ISO 2811-1)Pensity at 20 °C:1.361 g/cm³ (DIN EN ISO 2811-1)Relative densityNot determined.Vapour densityNot determined.Vapour densityNot determined.Vapour densityNot determined.*Qapour densityNot determined.*Qapour densityNot determined.*Qapour densityProduct is not selfigniting.*Qapour dens		
Boiling point or initial boiling point and boiling range137-143 °C (1330-20-7 Xylene)FlammabilityFlammabile.Lower and upper explosion limit0.7 Vol % (64742-95-6 Hydrocarbons, C9, aromatics)Upper:7.5 Vol % (64742-95-6 Hydrocarbons, C9, aromatics)Flash point:24 °C (DIN EN ISO 1523:2002)Decomposition temperature:Not determined.pHNot determined.Viscosity:Not determined.Viscosity:Not determined.Viscosity:Not determined.SolubilityNot determined.water:Not determined.Partition coefficient n-octanol/water (log value)Not determined.Vapour pressure at 20 °C:6.7-8.2 hPa (1330-20-7 Xylene)Density and/or relative densityNot determined.Vapour densityNot determined.Vapour densityNot determined.Vapour densityNot determined.Vapour densityNot determined.Vapour densityNot determined.9.2 Other informationFluidAppearance:Form:Form:FluidImportant information on protection of health and environment, and on safety.Auto-legnition temperature:Product is not selfigniting.Explosive properties:Product is not selfigniting.Solvent content:*********************************		
range137-143 °C (1330-20-7 Xylene)FlammabilityFlammabile.Lower and upper explosion limitFlammabile.Lower and upper explosion limit0.7 Vol % (64742-95-6 Hydrocarbons, C9, aromatics)Upper:7.5 Vol % (64742-95-6 Hydrocarbons, C9, aromatics)Flash point:24 °C (DIN EN ISO 1523:2002)Decomposition temperature:Not determined.PHNot determined.Viscosity:Kinematic viscosity at 20 °CSolubility>95 s (DIN 53211/4)Matter:Not miscible or difficult to mix.Partition coefficient n-octanol/water (log value)Not determined.Vapour pressure at 20 °C:6.7-8.2 hPa (1330-20-7 Xylene)Density at 20 °C:1.361 g/cm³ (DIN EN ISO 2811-1)Relative densityNot determined.Density at 20 °C:1.361 g/cm³ (DIN EN ISO 2811-1)Relative densityNot determined.9.2 Other informationAppearance:Form:FluidImportant information on protection of health and environment, and on safety.Auto-ignition temperature:Product is not selfigniting.Explosive properties:Product is not selfigniting.Solvent content:You (EC)VOC (EC)33.31 %Solids content (weight-%):66.7 %Change in conditionHou determined.Evaporation rateNot determined.		
Flammability       Flammable.         Lower and upper explosion limit       0.7 Vol % (64742-95-6 Hydrocarbons, C9, aromatics)         Upper:       7.5 Vol % (64742-95-6 Hydrocarbons, C9, aromatics)         Flash point:       24 °C (DIN EN ISO 1523:2002)         Decomposition temperature:       Not determined.         PH       Not determined.         Viscosity:       Solubility         Water:       Not determined.         Solubility       Not determined.         Water:       Not determined.         Partition coefficient n-octanol/water (log value)       Not determined.         Vapour pressure at 20 °C:       6.7-8.2 hPa (1330-20-7 Xylene)         Density and/or relative density       Not determined.         Vapour density       Not determined.         Vapour density       Not determined.         Vapour density       Not determined.         9.2 Other information       Fluid         Important information on protection of health and environment, and on safety.       Product is not selfigniting.         Explosive properties:       Product is not selfigniting.         Solvent content:       33.31 %         Solids content (weight-%):       66.7 %         Change in condition       Keight and anondition         Evaporation rate		137-143 °C (1330-20-7 Xylene)
Lower and upper explosion limitLower:0.7 Vol % (64742-95-6 Hydrocarbons, C9, aromatics)Value of the explosion temperature:7.5 Vol % (64742-95-6 Hydrocarbons, C9, aromatics)Flash point:24 °C (DIN EN ISO 1523:2002)Decomposition temperature:Not determined.pHNot determined.Viscosity:		
Lower:0.7 Vol % (64742-95-6 Hydrocarbons, C9, aromatics)Upper:7.5 Vol % (64742-95-6 Hydrocarbons, C9, aromatics)Flash point:24 °C (DIN EN ISO 1523:2002)Decomposition temperature:Not determined.pHNot determined.Viscosity:Kinematic viscosity at 20 °CSolubility>95 s (DIN 53211/4)Dynamic:Not miscible or difficult to mix.Partition coefficient n-octanol/water (log value)Not determined.Vapour pressure at 20 °C:6.7-8.2 hPa (1330-20-7 Xylene)Density and/or relative densityNot determined.Density at 0 °C:1.361 g/cm³ (DIN EN ISO 2811-1)Relative densityNot determined.9.2 Other informationAppearance:Form:FluidImportant information on protection of health and environment, and on safety.Auto-ignition temperature:Product is not selfigniting.Explosive properties:Product is not selfigniting.Solvent content:YoC (EC)Solvent content:3.31 %YoC (EC)33.31 %Change in conditionFuerwined.Evaporation rateNot determined.		
Upper:7.5 Vol % (64742-95-6 Hydrocarbons, C9, aromatics)Flash point:24 °C (DIN EN ISO 1523:2002)Decomposition temperature:Not determined.pHNot determined.Viscosity:Kinematic viscosity at 20 °CSolubility>95 s (DIN 53211/4)water:Not determined.Partition coefficient n-octanol/water (log value)Not determined.Vapour pressure at 20 °C:6.7-8.2 hPa (1330-20-7 Xylene)Density at 20 °C:1.361 g/cm³ (DIN EN ISO 2811-1)Relative densityNot determined.Partition coefficient n-octanol/water (log value)Not determined.Vapour pressure at 20 °C:1.361 g/cm³ (DIN EN ISO 2811-1)Relative densityNot determined.Pensity at 20 °C:1.361 g/cm³ (DIN EN ISO 2811-1)Relative densityNot determined.9.2 Other informationFluidAppearance:FluidForm:FluidImportant information on protection of health and environment, and on safety.Auto-ignition temperature:Product is not selfigniting.Explosive properties:Product is not selfigniting.Solvent content:33.31 %VOC (EC)33.31 %Solids content (weight-%):66.7 %Change in conditionKot determined.		0.7 Val % (61712-05-6 Hydrocarbons, CQ, aromatics)
Flash point:24 °C (DIN EN ISO 1523:2002)Decomposition temperature:Not determined.pHNot determined.Viscosity:Not determined.Kinematic viscosity at 20 °C>95 s (DIN 53211/4)Dynamic:Not determined.SolubilityNot determined.water:Not miscible or difficult to mix.Partition coefficient n-octanol/water (log value)Not determined.Vapour pressure at 20 °C:6.7-8.2 hPa (1330-20-7 Xylene)Density and/or relative densityNot determined.Density at 20 °C:1.361 g/cm³ (DIN EN ISO 2811-1)Relative densityNot determined.Vapour densityNot determined.9.2 Other informationFluidAppearance:FluidForm:FluidImportant information on protection of health and environment, and on safety.Product is not selfigniting.Auto-ignition temperature:Product is not selfigniting.Solvent content:Yoc (EC)33.31 %VOC (EC)33.31 %Solids content (weight-%):66.7 %Change in conditionKot determined.Evaporation rateNot determined.		
Decomposition temperature:Not determined.pHNot determined.Viscosity:Not determined.Kinematic viscosity at 20 °C>95 s (DIN 53211/4)Dynamic:Not determined.SolubilityNot miscible or difficult to mix.Partition coefficient n-octanol/water (log value)Not determined.Vapour pressure at 20 °C:6.7-8.2 hPa (1330-20-7 Xylene)Density and/or relative density6.7-8.2 hPa (1330-20-7 Xylene)Density at 20 °C:1.361 g/cm³ (DIN EN ISO 2811-1)Relative densityNot determined.Vapour densityNot determined.9.2 Other informationAppearance:Form:FluidImportant information on protection of health and environment, and on safety.Auto-ignition temperature:Product is not selfigniting.Explosive properties:Product is not selfigniting.Solvent content:33.31 %VOC (EC)33.31 %Solids content (weight-%):66.7 %Change in conditionKot determined.		
pHNot determined.Viscosity: Kinematic viscosity at 20 °C>95 s (DIN 53211/4)Dynamic: Solubility water:Not determined.Vapour pressure at 20 °C: Partition coefficient n-octanol/water (log value) Vapour pressure at 20 °C: Density and/or relative densityNot determined.Density and/or relative density Density at 20 °C:1.361 g/cm³ (DIN EN ISO 2811-1)Relative density Vapour densityNot determined.9.2 Other information Appearance: Form: Important information on protection of health and environment, and on safety.FluidAuto-ignition temperature: VOC (EC)Product is not selfigniting. Product is not explosive. However, formation of explosive air/vapour mixtures are possible.Solvent content: VOC (EC)33.31 % 66.7 %Solids content (weight-%): Exaporation rateNot determined.	•	
Viscosity:       >95 s (DIN 53211/4)         Minematic viscosity at 20 °C       >95 s (DIN 53211/4)         Dynamic:       Not determined.         Solubility       water:         water:       Not miscible or difficult to mix.         Partition coefficient n-octanol/water (log value)       Not determined.         Vapour pressure at 20 °C:       6.7-8.2 hPa (1330-20-7 Xylene)         Density and/or relative density       0         Density at 20 °C:       1.361 g/cm³ (DIN EN ISO 2811-1)         Relative density       Not determined.         Vapour density       Not determined.         Vapour density       Not determined.         9.2 Other information       Appearance:         Form:       Fluid         Important information on protection of health and environment, and on safety.       Product is not selfigniting.         Auto-ignition temperature:       Product is not selfigniting.         Explosive properties:       Product is not explosive. However, formation of explosive air/vapour mixtures are possible.         Solvent content:       VOC (EC)       33.31 %         Solids content (weight-%):       66.7 %         Change in condition       Evaporation rate		
Kinematic viscosity at 20 °C>95 s (DIN 53211/4)Dynamic:Not determined.SolubilityNot miscible or difficult to mix.water:Not miscible or difficult to mix.Partition coefficient n-octanol/water (log value)Not determined.Vapour pressure at 20 °C:6.7-8.2 hPa (1330-20-7 Xylene)Density and/or relative density6.7-8.2 hPa (DIN EN ISO 2811-1)Relative densityNot determined.Vapour densityNot determined.9.2 Other informationAppearance:Form:FluidImportant information on protection of health and environment, and on safety.Auto-ignition temperature:Product is not selfigniting.Explosive properties:Product is not selfigniting.Solvent content:3.31 %VOC (EC)33.31 %Solids content (weight-%):66.7 %Evaporation rateNot determined.		Not determined.
Dynamic:Not determined.SolubilityNot miscible or difficult to mix.Partition coefficient n-octanol/water (log value)Not determined.Partition coefficient n-octanol/water (log value)Not determined.Vapour pressure at 20 °C:6.7-8.2 hPa (1330-20-7 Xylene)Density and/or relative densityNot determined.Density at 20 °C:1.361 g/cm³ (DIN EN ISO 2811-1)Relative densityNot determined.Vapour densityNot determined.Vapour densityNot determined.9.2 Other informationAppearance:Form:FluidImportant information on protection of health and environment, and on safety.Auto-ignition temperature:Product is not selfigniting.Explosive properties:Product is not explosive. However, formation of explosive air/vapour mixtures are possible.Solvent content:YOC (EC)YOC (EC)33.31 %Solids content (weight-%):66.7 %Evaporation rateNot determined.		
SolubilityNot miscible or difficult to mix.water:Not miscible or difficult to mix.Partition coefficient n-octanol/water (log value)Not determined.Vapour pressure at 20 °C:6.7-8.2 hPa (1330-20-7 Xylene)Density and/or relative densityImage: Comparison of the end of		
water:Not miscible or difficult to mix.Partition coefficient n-octanol/water (log value)Not determined.Vapour pressure at 20 °C:6.7-8.2 hPa (1330-20-7 Xylene)Density and/or relative density1.361 g/cm³ (DIN EN ISO 2811-1)Relative densityNot determined.Vapour densityNot determined.Vapour densityNot determined.9.2 Other informationFluidAppearance:Form:Form:FluidImportant information on protection of health and environment, and on safety.Product is not selfigniting.Auto-ignition temperature:Product is not selfigniting.Solvent content:YoOur mixtures are possible.VOC (EC)33.31 %Solids content (weight-%):66.7 %Change in conditionKeyporation rate		Not determined.
Partition coefficient n-octanol/water (log value) Vapour pressure at 20 °C: Density and/or relative densityNot determined. 6.7-8.2 hPa (1330-20-7 Xylene)Density at 20 °C: Density at 20 °C:1.361 g/cm³ (DIN EN ISO 2811-1)Relative density Vapour densityNot determined. Not determined.Vapour densityNot determined.Vapour densityNot determined.9.2 Other information Appearance: Form:FluidProment, and on safety.FluidAuto-ignition temperature: Explosive properties:Product is not selfigniting.Solvent content: VOC (EC)33.31 %Solids content (weight-%): Exaporation rate66.7 %Change in conditionNot determined.	-	
Vapour pressure at 20 °C:6.7-8.2 hPa (1330-20-7 Xylene)Density and/or relative density1.361 g/cm³ (DIN EN ISO 2811-1)Relative densityNot determined.Vapour densityNot determined.Vapour densityNot determined.9.2 Other informationAppearance:Form:FluidImportant information on protection of health and environment, and on safety.Auto-ignition temperature:Product is not selfigniting.Explosive properties:Product is not explosive. However, formation of explosive air/vapour mixtures are possible.Solvent content:33.31 %VOC (EC)33.31 %Solids content (weight-%):66.7 %Change in conditionNot determined.		
Density and/or relative density         Density at 20 °C:       1.361 g/cm³ (DIN EN ISO 2811-1)         Relative density       Not determined.         Vapour density       Not determined.         9.2 Other information       Appearance:         Form:       Fluid         Important information on protection of health and environment, and on safety.       Product is not selfigniting.         Auto-ignition temperature:       Product is not explosive. However, formation of explosive air/vapour mixtures are possible.         Solvent content:       33.31 %         VOC (EC)       33.31 %         Solids content (weight-%):       66.7 %         Change in condition       Not determined.		
Density at 20 °C:1.361 g/cm³ (DIN EN ISO 2811-1)Relative densityNot determined.Vapour densityNot determined.9.2 Other informationFluidAppearance:FluidForm:FluidImportant information on protection of health and environment, and on safety.Auto-ignition temperature:Product is not selfigniting.Explosive properties:Product is not explosive. However, formation of explosive air/vapour mixtures are possible.Solvent content:33.31 %VOC (EC)33.31 %Solids content (weight-%):66.7 %Change in conditionNot determined.		6.7-8.2 hPa (1330-20-7 Xylene)
Relative density       Not determined.         Vapour density       Not determined.         Vapour density       Not determined.         9.2 Other information       Appearance:         Form:       Fluid         Important information on protection of health and environment, and on safety.       Fluid         Auto-ignition temperature:       Product is not selfigniting.         Explosive properties:       Product is not explosive. However, formation of explosive air/vapour mixtures are possible.         Solvent content:       VOC (EC)         Solids content (weight-%):       66.7 %         Change in condition       Not determined.		
Vapour density       Not determined.         9.2 Other information       Appearance:         Form:       Fluid         Important information on protection of health and environment, and on safety.       Fluid         Auto-ignition temperature:       Product is not selfigniting.         Explosive properties:       Product is not explosive. However, formation of explosive air/vapour mixtures are possible.         Solvent content:       33.31 %         VOC (EC)       33.31 %         Solids content (weight-%):       66.7 %         Change in condition       Not determined.		
<ul> <li>9.2 Other information</li> <li>Appearance:</li> <li>Form:</li> <li>Form:</li> <li>Fluid</li> <li>Important information on protection of health and environment, and on safety.</li> <li>Auto-ignition temperature:</li> <li>Product is not selfigniting.</li> <li>Explosive properties:</li> <li>Solvent content:</li> <li>VOC (EC)</li> <li>Solids content (weight-%):</li> <li>Change in condition</li> <li>Evaporation rate</li> <li>Not determined.</li> </ul>		
Appearance:       Fluid         Form:       Fluid         Important information on protection of health and environment, and on safety.       Fluid         Auto-ignition temperature:       Product is not selfigniting.         Explosive properties:       Product is not explosive. However, formation of explosive air/vapour mixtures are possible.         Solvent content:       Solids content (weight-%):         Solids content (weight-%):       66.7 %         Change in condition       Not determined.	· Vapour density	Not determined.
Appearance:       Fluid         Form:       Fluid         Important information on protection of health and environment, and on safety.       Product is not selfigniting.         Auto-ignition temperature:       Product is not selfigniting.         Explosive properties:       Product is not explosive. However, formation of explosive air/vapour mixtures are possible.         Solvent content:       Solids content (weight-%):         Solids content (weight-%):       66.7 %         Change in condition       Not determined.	9.2 Other information	
Form:       Fluid         Important information on protection of health and environment, and on safety.       Product is not selfigniting.         Auto-ignition temperature:       Product is not selfigniting.         Explosive properties:       Product is not explosive. However, formation of explosive air/vapour mixtures are possible.         Solvent content:       33.31 %         Solids content (weight-%):       66.7 %         Change in condition       Not determined.	· Appearance:	
environment, and on safety.Auto-ignition temperature:Product is not selfigniting.Explosive properties:Product is not explosive. However, formation of explosive air/vapour mixtures are possible.Solvent content:33.31 %VOC (EC)33.31 %Solids content (weight-%):66.7 %Change in conditionNot determined.	• •	Fluid
environment, and on safety.         Auto-ignition temperature:       Product is not selfigniting.         Explosive properties:       Product is not explosive. However, formation of explosive air/vapour mixtures are possible.         Solvent content:       33.31 %         VOC (EC)       33.31 %         Solids content (weight-%):       66.7 %         Change in condition       Not determined.	· Important information on protection of health an	d
Auto-ignition temperature:       Product is not selfigniting.         Explosive properties:       Product is not explosive. However, formation of explosive air/vapour mixtures are possible.         Solvent content:       33.31 %         VOC (EC)       33.31 %         Solids content (weight-%):       66.7 %         Change in condition       Not determined.		
Explosive properties:       Product is not explosive. However, formation of explosive air/vapour mixtures are possible.         Solvent content:       33.31 %         VOC (EC)       33.31 %         Solids content (weight-%):       66.7 %         Change in condition       Not determined.		Product is not selfigniting.
Solvent content:       air/vapour mixtures are possible.         VOC (EC)       33.31 %         Solids content (weight-%):       66.7 %         Change in condition       Evaporation rate         Not determined.       Not determined.		
Solvent content:         VOC (EC)       33.31 %         Solids content (weight-%):       66.7 %         Change in condition         Evaporation rate       Not determined.	· · · · · · · · · · · · · · · · · · ·	
• VOC (EC)       33.31 %         • Solids content (weight-%):       66.7 %         • Change in condition          • Evaporation rate       Not determined.	· Solvent content:	, , ,
Solids content (weight-%):       66.7 %         Change in condition       66.7 %         Evaporation rate       Not determined.		33.31 %
• Change in condition         • Evaporation rate       Not determined.		
Evaporation rate     Not determined.		
-		Not determined.

Page 6/11



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 01.02.2023

Trade name: FEYALKYD 303 Plasto-Coat

		(Conta: of page
Information with regard to physical hazard cl	lasses	
Explosives	Void	
Flammable gases	Void	
Aerosols	Void	
Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Flammable liquid and vapour.	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit flamma	able	
gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

#### **SECTION 10: Stability and reactivity**

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.

• 10.6 Hazardous decomposition products: Carbon monoxide

#### **SECTION 11: Toxicological information**

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

 $\cdot$  Acute toxicity Based on available data, the classification criteria are not met.

Skin corrosion/irritation Causes skin irritation.

· Serious eye damage/irritation Causes serious eye damage.

- STOT-single exposure May cause respiratory irritation.
- **STOT-repeated exposure** May cause damage to organs through prolonged or repeated exposure.

· 11.2 Information on other hazards

• Endocrine disrupting properties

78-93-3 Methyl ethyl ketone

#### **SECTION 12: Ecological information**

· 12.1 Toxicity

· Aquatic toxicity: No further relevant information available.

• **12.2 Persistence and degradability** No further relevant information available.

(Contd. on page 8)

(Contd. of page 6)

List II

Page 7/11

<sup>-</sup> GB



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 01.02.2023

(Contd. of page 7)

Trade name: FEYALKYD 303 Plasto-Coat

· 12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

• **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.

- 12.7 Other adverse effects
- · Remark: Toxic for fish

· Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) : hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

#### **SECTION 13: Disposal considerations**

#### · 13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

#### · Uncleaned packaging:

· Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

14.1 UN number or ID number ADR, IMDG, IATA	UN1263
14.2 UN proper shipping name	
ADR	UN1263 PAINT, ENVIRONMENTALLY HAZARDOUS
IMDG	PAINT (Trizinc bis(orthophosphate), Solvent naphtha MARINE POLLUTANT
ΙΑΤΑ	PAINT
14.3 Transport hazard class(es)	
ADR	
Class	3 (F1) Flammable liquids.

Page 8/11



Page 9/11

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 01.02.2023

Trade name: FEYALKYD 303 Plasto-Coat

	(Contd. of page 8)
· Label	3
·IMDG	
Class	3 Flammable liquids.
Label	3
IATA	
Class	3 Flammable liquids.
	3
<sup>·</sup> 14.4 Packing group <sup>·</sup> ADR, IMDG, IATA	III
· 14.5 Environmental hazards:	Product contains environmentally hazardous substances:
· Marine pollutant:	Trizinc bis(orthophosphate) Symbol (fish and tree)
<sup>•</sup> Special marking (ADR):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	30
EMS Number: Stowage Category	F-E, <u>S-E</u> A
14.7 Maritime transport in bulk according to IM instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Transport category Tunnel restriction code	3 D/E
Remarks:	$\leq 5$ I: 2.2.3.1.5 ADR
·IMDG	
· Limited quantities (LQ)	5L
Remarks:	≤ 5 l: 2.2.3.1.5 IMDG
UN "Model Regulation":	UN 1263 PAINT, 3, III, ENVIRONMENTALLY HAZARDOUS

### **SECTION 15: Regulatory information**

 $\cdot$  15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 01.02.2023

Trade name: FEYALKYD 303 Plasto-Coat

(Contd. of page 9)

Seveso category

E2 Hazardous to the Aquatic Environment P5c FLAMMABLE LIQUIDS

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %
NK	25-50

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H360Fd May damage fertility. Suspected of damaging the unborn child.
- H361d Suspected of damaging the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

#### Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

#### Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 2: Flammable liquids Category 2
- Flam. Liq. 3: Flammable liquids Category 3
- Acute Tox. 4: Acute toxicity Category 4

GB



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 01.02.2023

(Contd. of page 10)

Trade name: FEYALKYD 303 Plasto-Coat

Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Skin Sens. 1A: Skin sensitisation – Category 1A Repr. 1B: Reproductive toxicity – Category 1B Repr. 2: Reproductive toxicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3 \* \* Data compared to the previous version altered.

GB -

Page 11/11