

Page 1/10

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.02.2023 Version number 5 (replaces version 4) Revision: 01.02.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: FEYCOLUX 365 SATIN
- 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Paint
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

FEYCOLOR GmbH Maxhüttenstraße 6 93055 Regensburg Germany

Tel.: +49 (0) 941-60497-0 Fax: +49 (0) 941-60497-30

info@feycolor.com www.feycolor.com

Office hours:

Monday - Thursday: 08:00 - 12:00 und 13:00 - 16:00

Friday: 08:00 - 12:00

Email: sd@feycolor.com www.feycolor.com

• 1.4 Emergency telephone number: +49 (0) 700 24 11 21 12 (FCM)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms





GHS02 GHS07

· Signal word Warning

(Contd. on page 2)





according to 1907/2006/EC, Article 31

Printing date 01.02.2023 Version number 5 (replaces version 4) Revision: 01.02.2023

Trade name: FEYCOLUX 365 SATIN

(Contd. of page 1)

· Hazard-determining components of labelling:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

2-Methoxy-1-methylethyl acetate Hydrocarbons, C9, aromatics

n-Butyl acetate

Hazard statements

H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction. H336 May cause drowsiness or dizziness.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or

shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

SECTION 3: Composition/information on ingredients

- 2.3 Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
EC number: 919-857-5 Reg.nr.: 01-2119463258-33	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics ♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ STOT SE 3, H336, EUH066	10-25%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-Methoxy-1-methylethyl acetate ♦ Flam. Liq. 3, H226; ♦ STOT SE 3, H336	2.5-<10%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-Butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336, EUH066	1-<2.5%
CAS: 64742-95-6 EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Hydrocarbons, C9, aromatics ♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411; ♦ STOT SE 3, H335-H336, EUH066	1-<2.5%
EC number: 918-481-9 Reg.nr.: 01-2119457273-39	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics \$\infty\$ Asp. Tox. 1, H304, EUH066	<2.5%
		Contd. on page 3)

GB





according to 1907/2006/EC, Article 31

Printing date 01.02.2023 Version number 5 (replaces version 4) Revision: 01.02.2023

Trade name: FEYCOLUX 365 SATIN

		(Contd. of page 2)
CAS: 2457-01-4	barium bis(2-ethylhexanoate)	<1%
EINECS: 219-535-8	♠ Repr. 2, H361d; ♦ Eye Dam. 1, H318; ♦ Acute Tox. 4, H302; Acute Tox. 4, H332	
CAS: 85-44-9	Phthalic anhydride	≥0.1-<1%
EINECS: 201-607-5 Reg.nr.: 01-2119457017-41	♠ Resp. Sens. 1, H334; ♠ Eye Dam. 1, H318; ♠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	
CAS: 22464-99-9	2-ethylhexanoic acid, zirconium salt	<1%
EINECS: 245-018-1 Reg.nr.: 01-2119979088-21	♣ Repr. 2, H361d	
CAS: 85203-81-2	Hexanoic acid, 2-ethyl-, zinc salt, basic	<1%
EINECS: 286-272-3	♦ Repr. 2, H361d; ♦ Eye Irrit. 2, H319; Aquatic Chronic 3, H412	1
CAS: 136-52-7	cobalt bis(2-ethylhexanoate)	≥0.1-<0.25%
EINECS: 205-250-6	Repr. 1B, H360Fd; Aquatic Acute 1, H400; Eye Irrit. 2, H319; Skin Sens. 1A, H317; Aquatic Chronic 3, H412	1
Neg.III 01-2119324070-29	11313, Okiil Selis. 1A, 11317, Aquatic Official S, 11412	

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Immediately rinse with water.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 4)





according to 1907/2006/EC, Article 31

Printing date 01.02.2023 Version number 5 (replaces version 4) Revision: 01.02.2023

Trade name: FEYCOLUX 365 SATIN

(Contd. of page 3)

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

 Ingredients with limit values the 	it require monitoring	g at the workplace
---	-----------------------	--------------------

108-65-6 2-Methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm

Sk

123-86-4 n-Butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

136-52-7 cobalt bis(2-ethylhexanoate)

WEL Long-term value: 0.1 mg/m³ as Co; Carc, Sen

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

(Contd. on page 5)





according to 1907/2006/EC, Article 31

Printing date 01.02.2023 Version number 5 (replaces version 4) Revision: 01.02.2023

Trade name: FEYCOLUX 365 SATIN

· Respiratory protection:





In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Fluid

· Colour: According to product specification

· Odour: Characteristic
· Odour threshold: Not determined.

• Melting point/freezing point: Undetermined.

Boiling point or initial boiling point and boiling
 range
 155 °C (Hydrocarbons, C9-C11, n-alkanes, isoalkanes,

cyclics, < 2% aromatics)

• Flammability

Flammable.

· Lower and upper explosion limit · Lower: Not determined.

· **Lower:** Not determined. · **Upper:** Not determined.

Flash point: 24 °C (DIN EN ISO 1523:2002)

Ignition temperature: >200 °C (DIN 51794)
 Decomposition temperature: Not determined.
 pH Not determined.

· Viscosity: · Kinematic viscosity at 20 °C >200 s (DIN 53211/4)

• **Dynamic:** Not determined.

(Contd. on page 6)





according to 1907/2006/EC, Article 31

Printing date 01.02.2023 Version number 5 (replaces version 4) Revision: 01.02.2023

Trade name: FEYCOLUX 365 SATIN

(Contd. of page 5)

· Solubility

• water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value) Not determined.

· Vapour pressure at 20 °C: 3 hPa (Hydrocarbons, C9-C11, n-alkanes, isoalkanes,

cyclics, < 2% aromatics)

Density and/or relative density

Density at 20 °C: 1.185 g/cm³ (DIN EN ISO 2811-1)

Relative densityVapour densityNot determined.Not determined.

· 9.2 Other information

· Appearance:

· Form: Fluid

 \cdot Important information on protection of health and

environment, and on safety.

· **Auto-ignition temperature:** Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of explosive

air/vapour mixtures are possible.

· Solvent content:

· VOC (EC) 30.05 % Solids content (weight-%): 69.7 %

· Change in condition

• Evaporation rate Not determined.

· Information with regard to physical hazard classes

Explosives
Flammable gases
Aerosols
Oxidising gases
Gases under pressure
Void
Void

• Flammable liquids Flammable liquid and vapour.

Flammable solids Void
Self-reactive substances and mixtures Void
Pyrophoric liquids Void
Pyrophoric solids Void
Self-heating substances and mixtures Void

· Substances and mixtures, which emit flammable gases in contact with water

gases in contact with water Void
Oxidising liquids Void
Oxidising solids Void
Organic peroxides Void
Corrosive to metals Void
Desensitised explosives Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.

(Contd. on page 7)





according to 1907/2006/EC, Article 31

Printing date 01.02.2023 Version number 5 (replaces version 4) Revision: 01.02.2023

Trade name: FEYCOLUX 365 SATIN

(Contd. of page 6)

- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- STOT-single exposure May cause drowsiness or dizziness.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

78-93-3 Methyl ethyl ketone

List II

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB**: Not applicable.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packaging:
- · Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information · 14.1 UN number or ID number · ADR, IMDG, IATA UN1263 · 14.2 UN proper shipping name · ADR **UN1263 PAINT**

(Contd. on page 8)





according to 1907/2006/EC, Article 31

Printing date 01.02.2023 Version number 5 (replaces version 4) Revision: 01.02.2023

Trade name: FEYCOLUX 365 SATIN

	(Contd. of page 7
· IMDG, IATA	PAINT
· 14.3 Transport hazard class(es)	
· ADR	
· Class	3 (F1) Flammable liquids.
· Label	3
· IMDG, IATA	
Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group · ADR, IMDG, IATA	III
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	30
· EMS Number: · Stowage Category	F-E, <u>S-E</u> A
· 14.7 Maritime transport in bulk according to IM	
instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
Transport category	3
Tunnel restriction code	D/E
· Remarks:	≤ 450 l: 2.2.3.1.5 ADR
· IMDG · Limited quantities (LQ) · Remarks:	5L ≤ 30 l: 2.2.3.5 IMDG-Code
· UN "Model Regulation":	UN 1263 PAINT, 3, III
-	

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

(Contd. on page 9)





according to 1907/2006/EC, Article 31

Printing date 01.02.2023 Version number 5 (replaces version 4) Revision: 01.02.2023

Trade name: FEYCOLUX 365 SATIN

(Contd. of page 8)

- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- National regulations:
- · Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %
I	<1
NK	25-50

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

	H226	Flammable liquid and vapour.
--	------	------------------------------

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H360Fd May damage fertility. Suspected of damaging the unborn child.

H361d Suspected of damaging the unborn child.

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)
PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

Repr. 1B: Reproductive toxicity - Category 1B

Repr. 2: Reproductive toxicity – Category 2

(Contd. on page 10)



Page 10/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.02.2023 Version number 5 (replaces version 4) Revision: 01.02.2023

Trade name: FEYCOLUX 365 SATIN

(Contd. of page 9)

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

* Data compared to the previous version altered.

GB ·