

according to 1907/2006/EC, Article 31

Printing date 05.07.2021

Version number 2

Revision: 05.07.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking 1.1 Product identifier Trade name: FEYCOMASTIC 655 2K PU Klarlack UFI: 0N70-706D-K00T-QTKN

- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Clear coating material, Varnish

• **1.3 Details of the supplier of the safety data sheet** • **Manufacturer/Supplier:** FEYCOLOR GmbH Maxhüttenstraße 6 93055 Regensburg Germany

Tel.: +49 (0) 941-60497-0 Fax: +49 (0) 941-60497-30 info@feycolor.com www.feycolor.com

Office hours: Monday - Thursday: 08:00 - 12:00 und 13:00 - 16:00 Friday: 08:00 - 12:00

Email: sd@feycolor.com www.feycolor.com • **1.4 Emergency telephone number:** +49 (0) 700 24 11 21 12 (FCM)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008

GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.

GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

 • 2.2 Label elements
 • Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.
 • Hazard pictograms



· Signal word Warning

(Contd. on page 2)

GB



Printing date 05.07.2021

Safety data sheet

according to 1907/2006/EC, Article 31 Version number 2

Revision: 05.07.2021

Trade name: FEYCOMASTIC 655 2K PU Klarlack

| | (Contd. of page 1) |
|------------------|---|
| · Hazard-determ | ining components of labelling: |
| n-Butyl acetate | |
| 2-Methoxy-1-me | ethylethyl acetate |
| · Hazard stateme | ents |
| H226 Flammable | e liquid and vapour. |
| H336 May cause | e drowsiness or dizziness. |
| Precautionary s | statements |
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P261 | Avoid breathing dust/fume/gas/mist/vapours/spray. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
| P303+P361+P35 | 53 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. |
| P304+P340 | IF INHALED: Remove person to fresh air and keep comfortable for breathing. |
| P312 | Call a POISON CENTER/doctor if you feel unwell. |
| Additional info | rmation: |
| EUH066 Repeat | ed exposure may cause skin dryness or cracking. |
| 2.3 Other hazar | rds |
| Results of PBT | and vPvB assessment |
| PBT: Not applic | cable. |

• **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

| · Dangerous components: | | |
|---|---|----------|
| CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29 | n-Butyl acetate Flam. Liq. 3, H226; (1) STOT SE 3, H336 | 25-50% |
| | 2-Methoxy-1-methylethyl acetate Flam. Liq. 3, H226; () STOT SE 3, H336 | 2.5-<10% |
| CAS: 112-07-2 EINECS: 203-933-3 Reg.nr.: 01-2119475112-47 | 2-Butoxyethyl acetate Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332 | 1-<2.5% |
| • Additional information: Fo | or the wording of the listed hazard phrases refer to section 16. | 1 |

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- · 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

(Contd. on page 3)

GB

Page 2/8



Printing date 05.07.2021

Safety data sheet

according to 1907/2006/EC, Article 31

Revision: 05.07.2021

(Contd. of page 2)

Version number 2

Trade name: FEYCOMASTIC 655 2K PU Klarlack

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

• Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- \cdot 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- · Information about fire and explosion protection:
- Keep ignition sources away Do not smoke.
- Protect against electrostatic charges.
- ·7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep container tightly sealed.

· Storage class: 3

•7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

• Additional information about design of technical facilities: No further data; see item 7.

· Ingredients with limit values that require monitoring at the workplace:

123-86-4 n-Butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

(Contd. on page 4)

Page 3/8



according to 1907/2006/EC, Article 31

Printing date 05.07.2021

Version number 2

Revision: 05.07.2021

(Contd. of page 3)

Trade name: FEYCOMASTIC 655 2K PU Klarlack

108-65-6 2-Methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk

112-07-2 2-Butoxyethyl acetate

WEL Short-term value: 332 mg/m³, 50 ppm Long-term value: 133 mg/m³, 20 ppm Sk

· Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

· Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Breakthrough time of glove material

- The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

| 9.1 Information on basic physical and chemical properties General Information | | | | |
|--|------------------------------------|--|--|--|
| · Appearance: | | | | |
| Form: | Fluid | | | |
| Colour: | According to product specification | | | |
| · Odour: | Characteristic | | | |
| · Odour threshold: | Not determined. | | | |

(Contd. on page 5)

GR



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.07.2021

Version number 2

Revision: 05.07.2021

Trade name: FEYCOMASTIC 655 2K PU Klarlack

| | (Contd. of page 4 |
|---|--|
| · pH-value: | Not determined. |
| Change in condition Melting point/freezing point: Initial boiling point and boiling range | Undetermined. : 124 °C |
| · Flash point: | 24 °C (DIN EN ISO 1523:2002) |
| · Flammability (solid, gas): | Not applicable. |
| · Ignition temperature: | 315 °C (DIN 51794) |
| · Decomposition temperature: | Not determined. |
| · Auto-ignition temperature: | Product is not selfigniting. |
| • Explosive properties: | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. |
| · Explosion limits: Lower: Upper: | 1.2 Vol % 7.5 Vol % |
| · Vapour pressure at 20 °C: | 10.7 hPa |
| Density at 20 °C: Relative density Vapour density Evaporation rate | 0.988 g/cm ³ (DIN EN ISO 2811-1) Not determined. Not determined. Not determined. |
| · Solubility in / Miscibility with water: | Not miscible or difficult to mix. |
| · Partition coefficient: n-octanol/water: | Not determined. |
| · Viscosity: Dynamic: Kinematic at 20 °C: | Not determined. >30 s (DIN 53211/4) |
| · Solvent content: VOC (EC) | 43.40 % |
| Solids content (weight-%): | 56.2 % |
| · 9.2 Other information | No further relevant information available. |

SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

10.2 Chemical stability

- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

(Contd. on page 6)

GB



according to 1907/2006/EC, Article 31

Printing date 05.07.2021

Version number 2

Revision: 05.07.2021

(Contd. of page 5)

Trade name: FEYCOMASTIC 655 2K PU Klarlack

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.
- Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure
- May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) : slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

· Uncleaned packaging:

· Recommendation: Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information

· 14.1 UN-Number

· ADR, IMDG, IATA

UN1263

Page 6/8



according to 1907/2006/EC, Article 31

Printing date 05.07.2021

Version number 2

Revision: 05.07.2021

Trade name: FEYCOMASTIC 655 2K PU Klarlack

| | (Contd. of page |
|---|---|
| · 14.2 UN proper shipping name · ADR · IMDG, IATA | UN1263 PAINT PAINT |
| · 14.3 Transport hazard class(es) | |
| ADR | |
| | 2 (E1) Els associals listerida |
| · Class · Label | 3 (F1) Flammable liquids. |
| · IMDG, IATA | |
| · Class · Label | 3 Flammable liquids. 3 |
| · 14.4 Packing group · ADR, IMDG, IATA | III |
| · 14.5 Environmental hazards: | Not applicable. |
| 14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category | Warning: Flammable liquids. 30 F-E, <u>S-E</u> A |
| • 14.7 Transport in bulk according to Annex II of Ma and the IBC Code | arpol Not applicable. |
| · Transport/Additional information: | ** |
| · ADR · Limited quantities (LQ) · Transport category · Tunnel restriction code | 5L 3 D/E |
| · IMDG · Limited quantities (LQ) | 5L |
| · UN "Model Regulation": | UN 1263 PAINT, 3, III |

SECTION 15: Regulatory information

 \cdot 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P5c FLAMMABLE LIQUIDS

· Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

(Contd. on page 8)

GB

Page 7/8



Printing date 05.07.2021

Safety data sheet

according to 1907/2006/EC, Article 31 Version number 2

Revision: 05.07.2021

(Contd. of page 7)

Trade name: FEYCOMASTIC 655 2K PU Klarlack

• Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t • REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· National regulations:

· Additional classification according to Decree on Hazardous Materials, Annex II:

Class Share in %

NK 25-50

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

• Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative Flam. Lig. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Page 8/8