

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.02.2023

· 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Version number 7 (replaces version 6)

Revision: 01.02.2023

Page 1/9

# SECTION 1: Identification of the substance/mixture and of the company/undertaking · 1.1 Product identifier · Trade name: FEYCOPUR 629 2K-Decklack 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. · Application of the substance / the mixture Paint 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: **FEYCOLOR GmbH** Maxhüttenstraße 6 93055 Regensburg Germany Tel.: +49 (0) 941-60497-0 Fax: +49 (0) 941-60497-30 info@feycolor.com www.feycolor.com Office hours: Monday - Thursday: 08:00 - 12:00 und 13:00 - 16:00 Friday: 08:00 - 12:00 Email: sd@feycolor.com www.feycolor.com · 1.4 Emergency telephone number: +49 (0) 700 24 11 21 12 (FCM) **SECTION 2: Hazards identification** · 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 flame Flam. Liq. 3 H226 Flammable liquid and vapour. environment Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects. H317 May cause an allergic skin reaction. Skin Sens. 1 STOT SE 3 H336 May cause drowsiness or dizziness.

(Contd. on page 2)

GB -



Safety data sheet according to 1907/2006/EC, Article 31

Page 2/9

Printing date 01.02.2023

Version number 7 (replaces version 6)

Revision: 01.02.2023

### Trade name: FEYCOPUR 629 2K-Decklack

· Hazard pictog	(Contd. of page 1)
GHS02 GHS	
· Signal word W	/arning
Hydrocarbons, n-Butyl acetate 2-Methoxy-1-m Reaction mass • Hazard statem H226 Flammab H317 May caus H336 May caus H411 Toxic to a	ethylethyl acetate of pentamethyl-piperidyl sebacate nents ole liquid and vapour. se an allergic skin reaction. se drowsiness or dizziness. aquatic life with long lasting effects.
<ul> <li>Precautionary P210</li> </ul>	statements Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 P280 P303+P361+P3	Avoid breathing dust/fume/gas/mist/vapours/spray. Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. 353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P304+P340 P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
2.3 Other haza	ated exposure may cause skin dryness or cracking.
• <b>PBT:</b> Not applie • <b>vPvB:</b> Not app	cable.

#### **SECTION 3: Composition/information on ingredients**

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous	components:
-------------	-------------

Dangerous components.		
	Hydrocarbons, C9, aromatics	_ ≥2.5-≤20%
	n-Butyl acetate	_ <15%
	2-Methoxy-1-methylethyl acetate Flam. Liq. 3, H226;	_ 2.5-<10%
Reg.nr.: 01-2119491304-40	Reaction mass of pentamethyl-piperidyl sebacate Repr. 2, H361f;  Aquatic Acute 1, H400; Aquatic Chronic 1, H410;  Skin Sens. 1A, H317	_ ≥0.25-<1%
	(	Contd. on page 3



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 7 (replaces version 6)

Revision: 01.02.2023

(Contd. of page 2)

Page 3/9

Trade name: FEYCOPUR 629 2K-Decklack

· Additional information: For the wording of the listed hazard phrases refer to section 16.

#### **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation:
- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately rinse with water.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

#### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

#### **SECTION 6: Accidental release measures**

 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

• 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

- 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### **SECTION 7: Handling and storage**

#### • **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

(Contd. on page 4)



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 7 (replaces version 6)

Revision: 01.02.2023

(Contd. of page 3)

Trade name: FEYCOPUR 629 2K-Decklack

• **Information about fire - and explosion protection:** Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

• Requirements to be met by storerooms and receptacles: No special requirements.

- Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- 7.3 Specific end use(s) No further relevant information available.

#### **SECTION 8: Exposure controls/personal protection**

#### · 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

#### 123-86-4 n-Butyl acetate

WEL Short-term value: 966 mg/m<sup>3</sup>, 200 ppm Long-term value: 724 mg/m<sup>3</sup>, 150 ppm

#### 108-65-6 2-Methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m<sup>3</sup>, 100 ppm Long-term value: 274 mg/m<sup>3</sup>, 50 ppm Sk

• Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

#### · Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

GB





Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 7 (replaces version 6)

Revision: 01.02.2023

(Contd. of page 4)

Trade name: FEYCOPUR 629 2K-Decklack

· Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical propertie	s
9.1 Information on basic physical and chemical p	roperties
General Information	
· Physical state	Fluid
· Colour:	According to product specification
· Odour:	Characteristic
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling	
range	124-128 °C (123-86-4 n-Butyl acetate)
Flammability	Flammable.
Lower and upper explosion limit	
Lower:	0.7 Vol % (64742-95-6 Hydrocarbons, C9, aromatics)
Upper:	7.5 Vol % (64742-95-6 Hydrocarbons, C9, aromatics)
Flash point:	32 °C (DIN EN ISO 1523:2002)
Ignition temperature:	315 °C (DIN 51794)
Decomposition temperature:	Not determined.
pH	Not determined.
Viscosity:	
Kinematic viscosity at 20 °C	100-170 s (DIN 53211/4)
Dynamic:	Not determined.
Solubility	
water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure at 20 °C:	10.7 hPa (123-86-4 n-Butyl acetate)
Density and/or relative density	·····
Density at 20 °C:	1.087 g/cm³ (DIN EN ISO 2811-1)
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Form:	Fluid
Important information on protection of health an	a
environment, and on safety.	Des dust is wet as line it is a
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive
Colvert contents	air/vapour mixtures are possible.
Solvent content:	44 70 0/
VOC (EC)	41.76 %
	(Contd. on page

Page 5/9



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 7 (replaces version 6)

Revision: 01.02.2023

Trade name: FEYCOPUR 629 2K-Decklack

		(Contd. of page
Solids content (weight-%):	58.1 %	
Change in condition		
Evaporation rate	Not determined.	
Information with regard to physical hazard cl	lasses	
Explosives	Void	
Flammable gases	Void	
Aerosols	Void	
Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Flammable liquid and vapour.	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit flamma	able	
gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

#### **SECTION 10: Stability and reactivity**

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information		
• Acute to • Respirato • STOT-sin	rmation on hazard classes as defined in Regulation (EC) No 1272/2008 kicity Based on available data, the classification criteria are not met. Fory or skin sensitisation May cause an allergic skin reaction. Ingle exposure May cause drowsiness or dizziness. Ingle on other hazards	
· Endocrin	e disrupting properties	
556-67-2	octamethylcyclotetrasiloxane	List II, III
541-02-6	Decamethylcyclopentasiloxane	List II
540-97-6	Dodecamethylcyclohexasiloxane	List II
	•	GE

(Contd. on page 7)

Page 6/9



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 7 (replaces version 6)

Revision: 01.02.2023

(Contd. of page 6)

Trade name: FEYCOPUR 629 2K-Decklack

#### **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- 12.7 Other adverse effects
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) : hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies. Toxic for aquatic organisms

#### **SECTION 13: Disposal considerations**


#### · 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.





Page 8/9

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 7 (replaces version 6)

Revision: 01.02.2023

Trade name: FEYCOPUR 629 2K-Decklack

	(Contd. of page 7
<sup>.</sup> Label	3
· IMDG	
Class	3 Flammable liquids.
Label	3
IATA	
Class	3 Flammable liquids.
Label	3
· 14.4 Packing group · ADR, IMDG, IATA	III
<sup>·</sup> 14.5 Environmental hazards: <sup>·</sup> Marine pollutant: <sup>·</sup> Special marking (ADR):	Product contains environmentally hazardous substances: bis-(1,2,2,6,6-penthamethyl-4-piperidyl)sebacate Symbol (fish and tree) Symbol (fish and tree)
<ul> <li>14.6 Special precautions for user</li> <li>Hazard identification number (Kemler code):</li> <li>EMS Number:</li> <li>Stowage Category</li> </ul>	Warning: Flammable liquids. 30 F-E, <u>S-E</u> A
<ul> <li>14.7 Maritime transport in bulk according to IM instruments</li> </ul>	O Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ) Transport category Tunnel restriction code Remarks:	5L 3 D/E ≤ 5 l: 2.2.3.1.5 ADR
· IMDG · Limited quantities (LQ) · Remarks:	5L ≤ 5 l: 2.2.3.1.5 IMDG
UN "Model Regulation":	UN 1263 PAINT, 3, III, ENVIRONMENTALLY HAZARDOUS

#### **SECTION 15: Regulatory information**

 $\cdot$  15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 7 (replaces version 6)

Revision: 01.02.2023

Trade name: FEYCOPUR 629 2K-Decklack

(Contd. of page 8)

- Seveso category
   E2 Hazardous to the Aquatic Environment
   P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %
NK	25-50

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H317 May cause an allergic skin reaction.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H361f Suspected of damaging fertility.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

#### Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

#### Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3 Skin Sens. 1: Skin sensitisation - Category 1 Skin Sens. 1A: Skin sensitisation - Category 1A Repr. 2: Reproductive toxicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 \* Data compared to the previous version altered.

Page 9/9