

Safety data sheet

Page 1/10

according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 31.01.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

- · Trade name: FEYCOZINK 515 2K EP Zinkstaub
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- · Application of the substance / the mixture Paint
- · 1.3 Details of the supplier of the safety data sheet

• Manufacturer/Supplier: FEYCOLOR GmbH Maxhüttenstraße 6 93055 Regensburg Germany

Tel.: +49 (0) 941-60497-0 Fax: +49 (0) 941-60497-30 info@feycolor.com www.feycolor.com

Office hours: Monday - Thursday: 08:00 - 12:00 und 13:00 - 16:00 Friday: 08:00 - 12:00

Email: sd@feycolor.com www.feycolor.com

• 1.4 Emergency telephone number: +49 (0) 700 24 11 21 12 (FCM)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture
 Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.

corrosion

Eye Dam. 1 H318 Causes serious eye damage.

Aquatic Acute 1H400 Very toxic to aquatic life.Aquatic Chronic 1H410 Very toxic to aquatic life with long lasting effects.



Skin Irrit. 2H315 Causes skin irritation.Skin Sens. 1H317 May cause an allergic skin reaction.

(Contd. on page 2)

бB



Page 2/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 31.01.2023

(Contd. of page 1)

Trade name: FEYCOZINK 515 2K EP Zinkstaub

Hazard pictog	classified and labelled according to the GB CLP regulation. rams
GHS02 GHS	605 GHS07 GHS09
Signal word D	langer
	nining components of labelling:
Isobutanol	pichlorhydrin), epoxy resin (number average molecular weight 700-1100)
Hazard statem	
	ble liquid and vapour.
H315 Causes	
H318 Causes	serious eye damage.
H317 May caus	se an allergic skin reaction.
	c to aquatic life with long lasting effects.
Precautionary	
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read carefully and follow all instructions. 353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [c
P303+P301+P	shower].
P305+P351+P	338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,
10001100111	present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P321	Specific treatment (see on this label).
P362+P364	Take off contaminated clothing and wash it before reuse.
P501	Dispose of contents/container in accordance with local/regional/national/internationaregulations.
Additional info	
	ins epoxy constituents. May produce an allergic reaction.
2.3 Other haza	
	T and vPvB assessment
PBT: Not appli	cable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 7440-66-6	zinc powder - zinc dust (stabilized)	50-100%
EINECS: 231-175-3	Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
Reg.nr.: 01-2119467174-37		
CAS: 25068-38-6	Bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight 700-1100)	2.5-<10%
	♦ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205	otd on page 3

(Contd. on page 3) - GB



Page 3/10

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 31.01.2023

Trade name: FEYCOZINK 515 2K EP Zinkstaub

	(Cd	ontd. of page 2)
CAS: 78-83-1	Isobutanol	≥3-<10%
EINECS: 201-148-0 Reg.nr.: 01-2119484609-23	♦ Flam. Liq. 3, H226; ♦ Eye Dam. 1, H318; ♦ Skin Irrit. 2, H315; STOT SE 3, H335-H336	
CAS: 107-98-2 EINECS: 203-539-1	1-methoxy-2-propanol ∲ Flam. Liq. 3, H226;	2.5-<10%
Reg.nr.: 01-2119457435-35		
CAS: 108-65-6	2-Methoxy-1-methylethyl acetate	2.5-<10%
EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	🚸 Flam. Liq. 3, H226; 🚸 STOT SE 3, H336	
CAS: 1330-20-7	Xylene	1-<2.5%
EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	 Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. H319; STOT SE 3, H335 	
CAS: 64742-95-6	Hydrocarbons, C9, aromatics	1-<2.5%
EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Image State & State & Asp. Tox. 1, H304; Image & Aquatic Chronic 2, H411; Image & STOT SE 3, H335-H336, EUH066 Image & State	
• Additional information: Fo	r the wording of the listed hazard phrases refer to section 16.	

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation:

Supply fresh air and to be sure call for a doctor.

- In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

(Contd. on page 4)

GB



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 31.01.2023

(Contd. of page 3)

Trade name: FEYCOZINK 515 2K EP Zinkstaub

 Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water. 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent. Dispose contaminated material as waste according to item 13. Ensure adequate ventilation. 6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information. 	(Conta: of page 3)
SECTION 7: Handling and storage	
 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols. Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. 	
 7.2 Conditions for safe storage, including any incompatibilities Storage: Requirements to be met by storerooms and receptacles: No special requirements. Information about storage in one common storage facility: Store away from foodstuffs. Further information about storage conditions: Keep container tightly sealed. Storage class: 3 7.3 Specific end use(s) No further relevant information available. 	
SECTION 8: Exposure controls/personal protection	
· 8.1 Control parameters	
Ingredients with limit values that require monitoring at the workplace:	
78-83-1 Isobutanol WEL Short-term value: 231 mg/m³, 75 ppm Long-term value: 154 mg/m³, 50 ppm	
107-98-2 1-methoxy-2-propanol	
WEL Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm Sk	
108-65-6 2-Methoxy-1-methylethyl acetate	
WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk	
1330-20-7 Xylene	
WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV	
	(Contd. on page 5)

Page 4/10



Page 5/10

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 31.01.2023

(Contd. of page 4)

Trade name: FEYCOZINK 515 2K EP Zinkstaub

mmol/mol creatinine ium: urine upling time: post shift ameter: methyl hippuric acid
ipling time: post shift ameter: methyl hippuric acid
meter: methyl hippuric acid
· · · ·
nformation: The lists valid during the making were used as basis. re controls
engineering controls No further data; see item 7.
protection measures, such as personal protective equipment

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin.

Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

 Breakthrough time of glove material The exact break trough time has to be

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties		
• 9.1 Information on basic physical a	and chemical properties	
 Physical state 	Fluid	
· Colour:	According to product specification	
		(Contd. on page 6)
		GB -



Page 6/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 31.01.2023

Trade name: FEYCOZINK 515 2K EP Zinkstaub

	(Contd. of page
Odour:	Characteristic
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling	
range	906 °C (7440-66-6 zinc powder - zinc dust (stabilized))
Flammability	Flammable.
Lower and upper explosion limit	
Lower:	Not determined.
Upper:	Not determined.
Flash point:	24 °C (DIN EN ISO 1523:2002)
Ignition temperature:	630 °C (DIN 51794)
Decomposition temperature:	Not determined.
pH	Not determined.
Viscosity:	
Kinematic viscosity	Not determined.
Dynamic at 20 °C:	2,000 mPas
Solubility	2,000 mi do
water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure:	
	Not determined.
Density and/or relative density	
Density at 20 °C:	2.849 g/cm ³ (DIN EN ISO 2811-1)
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Form:	Fluid
Important information on protection of health a	nd
environment, and on safety.	
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosiv
	air/vapour mixtures are possible.
	all/vapour mixtures are possible.
Solvent content:	
Solvent content: VOC (EC)	15.11 %
VOC (EC)	15.11 %
VOC (EC) Solids content (weight-%):	15.11 %
VOC (EC) Solids content (weight-%): Change in condition Evaporation rate	15.11 % 84.9 % Not determined.
VOC (EC) Solids content (weight-%): Change in condition Evaporation rate Information with regard to physical hazard class	15.11 % 84.9 % Not determined.
VOC (EC) Solids content (weight-%): Change in condition Evaporation rate Information with regard to physical hazard class Explosives	15.11 % 84.9 % Not determined.
VOC (EC) Solids content (weight-%): Change in condition Evaporation rate Information with regard to physical hazard class Explosives Flammable gases	15.11 % 84.9 % Not determined. ses Void Void
VOC (EC) Solids content (weight-%): Change in condition Evaporation rate Information with regard to physical hazard class Explosives Flammable gases Aerosols	15.11 % 84.9 % Not determined. ses Void Void Void Void
VOC (EC) Solids content (weight-%): Change in condition Evaporation rate Information with regard to physical hazard class Explosives Flammable gases Aerosols Oxidising gases	15.11 % 84.9 % Not determined. ses Void Void Void Void Void
VOC (EC) Solids content (weight-%): Change in condition Evaporation rate Information with regard to physical hazard class Explosives Flammable gases Aerosols Oxidising gases Gases under pressure	15.11 % 84.9 % Not determined. Ses Void Void Void Void Void Void Void
VOC (EC) Solids content (weight-%): Change in condition Evaporation rate Information with regard to physical hazard class Explosives Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids	15.11 % 84.9 % Not determined. Ses Void Void Void Void Void Void Flammable liquid and vapour.
VOC (EC) Solids content (weight-%): Change in condition Evaporation rate Information with regard to physical hazard class Explosives Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids Flammable solids	15.11 % 84.9 % Not determined. Ses Void Void Void Void Void Flammable liquid and vapour. Void
VOC (EC) Solids content (weight-%): Change in condition Evaporation rate Information with regard to physical hazard class Explosives Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures	15.11 % 84.9 % Not determined. ies Void Void Void Void Void Void Flammable liquid and vapour. Void Void
VOC (EC) Solids content (weight-%): Change in condition Evaporation rate Information with regard to physical hazard class Explosives Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures Pyrophoric liquids	15.11 % 84.9 % Not determined. ies Void Void Void Void Void Void Flammable liquid and vapour. Void Void Void Void
VOC (EC) Solids content (weight-%): Change in condition Evaporation rate Information with regard to physical hazard class Explosives Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures	15.11 % 84.9 % Not determined. ies Void Void Void Void Void Void Flammable liquid and vapour. Void Void



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 31.01.2023

(Contd. of page 6)

Trade name: FEYCOZINK 515 2K EP Zinkstaub

		(Conta. of page 6)
Self-heating substances and mixtures	Void	
 Substances and mixtures, which emit fla 	mmable	
gases in contact with water	Void	
· Oxidising liquids	Void	
Oxidising solids	Void	
· Organic peroxides	Void	
Corrosive to metals	Void	
 Desensitised explosives 	Void	

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- 10.6 Hazardous decomposition products:

Possible in traces. Nitrogen oxides Hydrogen chloride (HCI) Carbon monoxide Nitrogen oxides (NOx)

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

- · Acute toxicity Based on available data, the classification criteria are not met.
- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye damage.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- · 11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

• Aquatic toxicity:

7440-66-6 zinc powder - zinc dust (stabilized)

EC50 (dynamic) 0.9 mg/kg (daphnia) (US EPA 821-R-02-012)

12.2 Persistence and degradability No further relevant information available.

- **12.3 Bioaccumulative potential** No further relevant information available.
- \cdot 12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

(Contd. on page 8)

GB



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 31.01.2023

(Contd. of page 7)

Trade name: FEYCOZINK 515 2K EP Zinkstaub

• **12.6 Endocrine disrupting properties** The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- **Remark:** Very toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) : hazardous for water Do not allow product to reach ground water, water course or sewage system. Must not reach sewage water or drainage ditch undiluted or unneutralised. Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies. Very toxic for aquatic organisms

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information · 14.1 UN number or ID number · ADR, IMDG, IATA UN1263 · 14.2 UN proper shipping name · ADR UN1263 PAINT, ENVIRONMENTALLY HAZARDOUS PAINT (zinc powder - zinc dust (stabilized), Solvent · IMDG naphtha), MARINE POLLUTANT ·IATA PAINT · 14.3 Transport hazard class(es) · ADR · Class 3 (F1) Flammable liquids. · Label 3 IMDG · Class 3 Flammable liquids. (Contd. on page 9) GB

Page 8/10



Page 9/10

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 31.01.2023

Trade name: FEYCOZINK 515 2K EP Zinkstaub

	(Contd. of page
Label	3
ΙΑΤΑ	
Class	3 Flammable liquids.
Label	3
14.4 Packing group	
ADR, IMDG, IATA	III
14.5 Environmental hazards:	
Marine pollutant: Special marking (ADR):	Symbol (fish and tree) Symbol (fish and tree)
14.6 Special precautions for user Hazard identification number (Kemler code):	Warning: Flammable liquids. 30
EMS Number:	F-E,S-E
Stowage Category	A
14.7 Maritime transport in bulk according to IM	
instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Transport category Tunnel restriction code	3 D/E
Remarks:	≤ 5 I: 2.2.3.1.5 ADR
IMDG	
Limited quantities (LQ)	5L
Remarks:	≤ 5 l: 2.2.3.1.5 IMDG
UN "Model Regulation":	UN 1263 PAINT, 3, III, ENVIRONMENTALL
-	HAZARDOUS

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

• Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category

E1 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

 \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements 100 t

 \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t

(Contd. on page 10)

- GB



Page 10/10

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 31.01.2023

Trade name: FEYCOZINK 515 2K EP Zinkstaub

· National regulations:

(Contd. of page 9)

Additional classification according to Decree on Hazardous Materials, Annex II:

Class | Share in %

NK 10-25

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

EUH205 Contains epoxy constituents. May produce an allergic reaction.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 3: Flammable liquids Category 3
- Acute Tox. 4: Acute toxicity Category 4
- Skin Irrit. 2: Skin corrosion/irritation Category 2
- Eye Dam. 1: Serious eye damage/eye irritation Category 1
- Eye Irrit. 2: Serious eye damage/eye irritation Category 2
- Skin Sens. 1: Skin sensitisation Category 1
- STOT SE 3: Specific target organ toxicity (single exposure) Category 3
- STOT RE 2: Specific target organ toxicity (repeated exposure) Category 2
- Asp. Tox. 1: Aspiration hazard Category 1

```
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1
```

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

* Data compared to the previous version altered.