

according to 1907/2006/EC, Article 31

Printing date 12.07.2021

Version number 2

Revision: 12.07.2021

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

### · 1.1 Product identifier

- · Trade name: RELAFLOOR 2500 2K EP HS Bindemittel für Colorquarz
- · UFI: XE01-E0DC-E00W-XD0H
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Coating

#### · 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: FEYCOLOR GmbH Maxhüttenstraße 6 93055 Regensburg Germany


Tel.: +49 (0) 941-60497-0 Fax: +49 (0) 941-60497-30 info@feycolor.com www.feycolor.com

Office hours: Monday - Thursday: 08:00 - 12:00 und 13:00 - 16:00 Friday: 08:00 - 12:00

Email: sd@feycolor.com www.feycolor.com • 1.4 Emergency telephone number: +49 (0) 700 24 11 21 12 (FCM)

### **SECTION 2: Hazards identification**

· 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008



Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

GHS07

Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



(Contd. on page 2)



according to 1907/2006/EC, Article 31

Printing date 12.07.2021

Version number 2

Revision: 12.07.2021

Trade name: RELAFLOOR 2500 2K EP HS Bindemittel für Colorquarz

~	(Contd. of page 1)
Signal word W	/arning
Hazard-deteri	mining components of labelling:
	ct: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight =< 700)
	oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol
	(C12-14-alkyloxy)methyl] derivs
Hazard staten	nents
H315 Causes sl	kin irritation.
H319 Causes se	erious eye irritation.
	se an allergic skin reaction.
H411 Toxic to	aquatic life with long lasting effects.
Precautionary	statements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves / eye protection / face protection.
P305+P351+P3	338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy
	to do. Continue rinsing.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
Additional inf	
	nins epoxy constituents. May produce an allergic reaction.
2.3 Other haza	
	Γ and vPvB assessment
<b>PBT:</b> Not appl	
vPvB: Not app	licable.

### **SECTION 3: Composition/information on ingredients**

#### · 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

#### · Dangerous components:

Dangerous components.					
	Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight =< 700)	50-100%			
Reg.nr.: 01-2119456619-26	Aquatic Chronic 2, H411; 🗘 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317				
CAS: 9003-36-5 NLP: 500-006-8	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	≥10-<25%			
Reg.nr.: 01-2119454392-40	Aquatic Chronic 2, H411; 🚸 Skin Irrit. 2, H315; Skin Sens. 1, H317				
CAS: 68609-97-2 EINECS: 271-846-8 Reg.nr.: 01-2119485289-22	oxirane, mono[(C12-14-alkyloxy)methyl] derivs	10-25%			
Additional informations For the wording of the listed harved almoses refer to section 16					

• Additional information: For the wording of the listed hazard phrases refer to section 16.

#### **SECTION 4: First aid measures**

#### · 4.1 Description of first aid measures

• General information: Immediately remove any clothing soiled by the product.

(Contd. on page 3) GB



according to 1907/2006/EC, Article 31

Printing date 12.07.2021

Version number 2

Revision: 12.07.2021

(Contd. of page 2)

Trade name: RELAFLOOR 2500 2K EP HS Bindemittel für Colorquarz

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

#### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

#### **SECTION 6: Accidental release measures**

• 6.1 Personal precautions, protective equipment and emergency procedures Not required.

#### · 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

- 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
  6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

- Prevent formation of aerosols.
- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Keep container tightly sealed.
- Storage class: 10
- 7.3 Specific end use(s) No further relevant information available.

(Contd. on page 4)

Page 3/9



according to 1907/2006/EC, Article 31

Printing date 12.07.2021

Version number 2

Revision: 12.07.2021

Trade name: RELAFLOOR 2500 2K EP HS Bindemittel für Colorquarz

(Contd. of page 3)

#### **SECTION 8: Exposure controls/personal protection**

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see item 7.
- · Ingredients with limit values that require monitoring at the workplace:
- The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

#### · Protection of hands:

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

#### • Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Breakthrough time of glove material

- The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- Eye protection:



Tightly sealed goggles

### **SECTION 9: Physical and chemical properties**

- 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:
- Form:
- Colour:
- Odour:

Fluid According to product specification Characteristic

(Contd. on page 5)

- GE



according to 1907/2006/EC, Article 31

Printing date 12.07.2021

Version number 2

Revision: 12.07.2021

#### Trade name: RELAFLOOR 2500 2K EP HS Bindemittel für Colorquarz

	(Contd. of page 4)
· Odour threshold:	Not determined.
· pH-value:	Not determined.
<sup>.</sup> Change in condition Melting point/freezing point: Initial boiling point and boiling range	Undetermined. : 201 °C
· Flash point:	130 °C (DIN EN ISO 1523:2002)
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	460 °C (DIN 51794)
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product does not present an explosion hazard.
· Explosion limits: Lower: Upper:	Not determined. Not determined.
· Vapour pressure at 20 °C:	<0.1 hPa
Density at 20 °C: Relative density Vapour density Evaporation rate	1.099 g/cm <sup>3</sup> (DIN EN ISO 2811-1) Not determined. Not determined. Not determined.
Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity: Dynamic at 20 °C: Kinematic:	1,100 mPas Not determined.
· Solvent content: VOC (EC)	0.00 %
Solids content (weight-%):	100.0 %
• 9.2 Other information	No further relevant information available.

### **SECTION 10: Stability and reactivity**

· 10.1 Reactivity No further relevant information available.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

Possible in traces.

Nitrogen oxides

Hydrogen chloride (HCl)

(Contd. on page 6)

<sup>· 10.2</sup> Chemical stability

<sup>·</sup> Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.



according to 1907/2006/EC, Article 31

Printing date 12.07.2021

Version number 2

Revision: 12.07.2021

(Contd. of page 5)

Trade name: RELAFLOOR 2500 2K EP HS Bindemittel für Colorquarz

Carbon monoxide Nitrogen oxides (NOx)

#### **SECTION 11: Toxicological information**

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

#### 25068-38-6 Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight =< 700)

Oral LD50 >5,000 mg/kg (rat)

Dermal LD50 >2,000 mg/kg (rabbit)

- · Primary irritant effect:
- · Skin corrosion/irritation
- Causes skin irritation.
- Serious eye damage/irritation
- Causes serious eye irritation.
- Respiratory or skin sensitisation
- May cause an allergic skin reaction. • Additional toxicological information:
- Additional toxicological information:
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- $\cdot$  STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

### **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) : hazardous for water

- Do not allow product to reach ground water, water course or sewage system.
- Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

- Toxic for aquatic organisms
- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- $\cdot$  12.6 Other adverse effects No further relevant information available.





according to 1907/2006/EC, Article 31

Printing date 12.07.2021

Version number 2

Revision: 12.07.2021

(Contd. of page 6)

Trade name: RELAFLOOR 2500 2K EP HS Bindemittel für Colorquarz

# **SECTION 13: Disposal considerations**

· 13.1 Waste treatment methods

· European waste catalogue

• Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

• **Recommendation:** Packagings that may not be cleansed are to be disposed of in the same manner as the product.

08 01 11\* waste paint and varnish containing organic solvents or other hazardous substances

<b>SECTION 14: Transport information</b>	
· 14.1 UN-Number · ADR, IMDG, IATA	UN3082
<ul> <li>14.2 UN proper shipping name</li> <li>ADR</li> </ul>	UN3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT)
· IMDG · IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT), MARINE POLLUTANT ENVIRONMENTALLY HAZARDOUS SUBSTANCE,
	LIQUID, N.O.S. (PAINT)
· 14.3 Transport hazard class(es) · ADR	
· Class · Label	9 (M6) Miscellaneous dangerous substances and articles. 9
· IMDG, IATA	
· Class · Label	9 Miscellaneous dangerous substances and articles. 9
· 14.4 Packing group · ADR, IMDG, IATA	III
· 14.5 Environmental hazards:	Product contains environmentally hazardous substances: hexamethylene diacrylate
• Marine pollutant: • Special marking (ADR):	Symbol (fish and tree) Symbol (fish and tree)
<ul> <li>Special marking (IATA):</li> <li>14.6 Special precautions for user</li> <li>Hazard identification number (Kemler code):</li> </ul>	Symbol (fish and tree) Warning: Miscellaneous dangerous substances and articles. 90
	(Contd. on page 8



according to 1907/2006/EC, Article 31

Printing date 12.07.2021

Version number 2

Revision: 12.07.2021

#### Trade name: RELAFLOOR 2500 2K EP HS Bindemittel für Colorquarz

	(Contd. of page 7)
· EMS Number:	F-A,S-F
· Stowage Category	А
· 14.7 Transport in bulk according to Annex II	of Marpol
and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Transport category	3
· Tunnel restriction code	-
· Remarks:	$\leq$ 51: SV 375 ADR
· IMDG	
· Limited quantities (LQ)	5L
· Remarks:	≤ 51: 2.10.2.7 IMDG-Code
· IATA	
· Remarks:	≤ 51: A 197
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT), 9, III

#### **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category E2 Hazardous to the Aquatic Environment
- $\cdot$  Qualifying quantity (tonnes) for the application of lower-tier requirements  $200\ t$
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

(Contd. on page 9)



Printing date 12.07.2021

### Safety data sheet

according to 1907/2006/EC, Article 31 Version number 2

Revision: 12.07.2021

(Contd. of page 8)

GB

Trade name: RELAFLOOR 2500 2K EP HS Bindemittel für Colorquarz

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Page 9/9