

according to 1907/2006/EC, Article 31

Printing date 12.07.2021

Version number 2

Revision: 08.10.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking · 1.1 Product identifier · Trade name: RELAMIX PLUS 207 Paste graualuminium 917 · UFI: 5C91-205N-900C-RVM7 · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. · Application of the substance / the mixture Stainer · 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: FEYCOLOR GmbH Maxhüttenstraße 6 93055 Regensburg Germany Tel.: +49 (0) 941-60497-0 Fax: +49 (0) 941-60497-30 info@feycolor.com www.feycolor.com Office hours: Monday - Thursday: 08:00 - 12:00 und 13:00 - 16:00 Friday: 08:00 - 12:00 Email: sd@feycolor.com www.feycolor.com • 1.4 Emergency telephone number: +49 (0) 700 24 11 21 12 (FCM) **SECTION 2: Hazards identification** · 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008 GHS02 flame Flam. Liq. 3 H226 Flammable liquid and vapour. GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

 • 2.2 Label elements
• Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.
• Hazard pictograms



· Signal word Warning

(Contd. on page 2)

GB



according to 1907/2006/EC, Article 31

Printing date 12.07.2021

Version number 2

Revision: 08.10.2020

(Contd. of page 1)

Trade name: RELAMIX PLUS 207 Paste graualuminium 917

Hazard-deter	mining components of labelling:
2-Methoxy-1-n	nethylethyl acetate
n-Butyl acetate	
Hazard staten	nents
H226 Flammal	ble liquid and vapour.
H336 May cau	se drowsiness or dizziness.
Precautionary	<i>v</i> statements
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P	353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/doctor if you feel unwell.
2.3 Other haz	ards
Results of PB	Γ and vPvB assessment
PBT · Not appl	licable

PBT: Not applicable.

5

• **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-Methoxy-1-methylethyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	25-50%
CAS: 7429-90-5 EINECS: 231-072-3 Reg.nr.: 01-2119529243-45	aluminium powder (stabilized)/ manufacturer classification	10-25%
CAS: 112-07-2 EINECS: 203-933-3 Reg.nr.: 01-2119475112-47	2-Butoxyethyl acetate Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	5-<10%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-Butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	2.5-<5%
• Additional information: Fo	or the wording of the listed hazard phrases refer to section 16.	

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.

(Contd. on page 3)

- GB



according to 1907/2006/EC, Article 31

Printing date 12.07.2021

Version number 2

Revision: 08.10.2020

(Contd. of page 2)

Trade name: RELAMIX PLUS 207 Paste graualuminium 917

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

• 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation. • 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- •7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 4)

GR

Page 3/9



Printing date 12.07.2021

Safety data sheet

according to 1907/2006/EC, Article 31 Version number 2

Revision: 08.10.2020

Trade name: RELAMIX PLUS 207 Paste graualuminium 917

	(Contd. of page 3)
Ingredients with limit values that require monitoring at the workplace:	
108-65-6 2-Methoxy-1-methylethyl acetate	
WEL Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm Sk	
7429-90-5 aluminium powder (stabilized)/ manufacturer classification	
WEL Long-term value: 10* 4** mg/m ³ *inhalable dust **respirable dust	
112-07-2 2-Butoxyethyl acetate	
WEL Short-term value: 332 mg/m ³ , 50 ppm Long-term value: 133 mg/m ³ , 20 ppm Sk	
123-86-4 n-Butyl acetate	
WEL Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm	
• Additional information: The lists valid during the making were used as basis.]

· 8.2 Exposure controls

- · Personal protective equipment:
- · General protective and hygienic measures:
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.

• Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

Page 4/9



Safety data sheet according to 1907/2006/EC, Article 31


Printing date 12.07.2021

Version number 2

Revision: 08.10.2020

(Contd. of page 4)

Trade name: RELAMIX PLUS 207 Paste graualuminium 917



*

Tightly sealed goggles

	handra hanna an d'an
• 9.1 Information on basic physical and c • General Information	hemical properties
· Appearance:	
Form:	Fluid
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	: 146.4 °C
Flash point:	41 °C (DIN 53213)
· Flammability (solid, gas):	Not applicable.
Ignition temperature:	280 °C (DIN 51794)
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixture are possible.
• Explosion limits:	
Lower:	1.5 Vol %
Upper:	10.8 Vol %
• Vapour pressure at 20 °C:	3.4 hPa
Density at 20 °C:	1.139 g/cm ³ (DIN 53217)
· Relative density	Not determined.
· Vapour density	Not determined.
Evaporation rate	Not determined.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 °C:	>40 s (ISO 6 mm)
· Solvent content: VOC (EC)	48.01 %

Page 5/9



according to 1907/2006/EC, Article 31

Printing date 12.07.2021

Version number 2

Revision: 08.10.2020

(Contd. of page 5)

Trade name: RELAMIX PLUS 207 Paste graualuminium 917

Solids content (weight-%):

•9.2 Other information

No further relevant information available.

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

52.0 %

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure
- May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- \cdot 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:
- Water hazard class 1 (German Regulation) : slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

(Contd. on page 7)

GB

Page 6/9



according to 1907/2006/EC, Article 31

Printing date 12.07.2021

Version number 2

Revision: 08.10.2020

(Contd. of page 6)

Trade name: RELAMIX PLUS 207 Paste graualuminium 917

· 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

· 14.1 UN-Number · ADR, IMDG, IATA	UN1263	
14.2 UN proper shipping name ADR IMDG, IATA	UN1263 PAINT PAINT	
14.3 Transport hazard class(es)		
ADR		
Class	3 (F1) Flammable liquids.	
Label	3	
· IMDG, IATA		
IMDG, IATA	3 Flammable liquids.	
IMDG, IATA		
IMDG, IATA	3 Flammable liquids.	
IMDG, IATA Class Label 14.4 Packing group ADR, IMDG, IATA 14.5 Environmental hazards:	3 Flammable liquids. 3	
IMDG, IATA Class Label 14.4 Packing group ADR, IMDG, IATA 14.5 Environmental hazards: Marine pollutant: 14.6 Special precautions for user	3 Flammable liquids. 3 III No Warning: Flammable liquids.	
IMDG, IATA Impose Class Label 14.4 Packing group ADR, IMDG, IATA 14.5 Environmental hazards: Marine pollutant: 14.6 Special precautions for user Hazard identification number (Kemler code):	3 Flammable liquids. 3 III No Warning: Flammable liquids. 30	
	3 Flammable liquids. 3 III No Warning: Flammable liquids.	

Page 7/9



Printing date 12.07.2021

Safety data sheet

according to 1907/2006/EC, Article 31 Version number 2

Revision: 08.10.2020

Trade name: RELAMIX PLUS 207 Paste graualuminium 917

	(Contd. of page '
· Transport/Additional information:		
· ADR		
· Limited quantities (LQ)	5L	
· Transport category	3	
• Tunnel restriction code	D/E	
· Remarks:	≤ 450 l: 2.2.3.1.5 ADR	
·IMDG		
Limited quantities (LQ)	5L	
Remarks:	≤ 30 l: 2.2.3.5 IMDG-Code	
· UN "Model Regulation":	UN 1263 PAINT, 3, III	

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

• DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· National regulations:

· Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %
NK	25-50

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.

H228 Flammable solid.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

· Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

(Contd. on page 9)

GB



Printing date 12.07.2021

Safety data sheet

according to 1907/2006/EC, Article 31 Version number 2

Revision: 08.10.2020

(Contd. of page 8)

Trade name: RELAMIX PLUS 207 Paste graualuminium 917

ICAO: International Civil Aviation Organisation ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids - Category 3 Flam. Sol. 1: Flammable solids - Category 1 Acute Tox. 4: Acute toxicity - Category 4 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 ** Data compared to the previous version altered. GB

Page 9/9